



# Quadro-Sicura® building owner's package

## Split heat pump

FOR BUILDINGS WITHOUT BASEMENTS

The solution for refrigerant lines for split heat pumps!



### APPLICATION

House-lead-ins for refrigerant lines  
Use in unfinished floor slabs to be made of waterproof concrete (white tank)

### PRODUCT ADVANTAGES

- Bend-resistant jacket pipe (inner diameter 110 mm/length 10 m) for compliance with bending radii
- Pipes and cables can be laid independently from construction progress
- Leak-tight against gas and pressing water
- Gasket insert is to be retrofitted around existing refrigerant lines
- With quick release for safe and secure closure

COMPONENTS/SCOPE OF DELIVERY



**Quadro-Secura® ADS DN 100**

Cast-in part for embedding in the floor slab,  
including bend-resistant jacket pipe (inner diame-  
ter 110 mm/length 10 m)

25  
Jahre  
Garantie



**Curaflex Nova® Uno/M/Z**

Gasket insert with replaceable onion ring  
inserts  
DN 100 for refrigerant lines and cables  
Including fixing tabs for easy installation

25  
Jahre  
Garantie



**ACCESSORIES – OPTIONAL**

- ITL nut set

Quadro-Secura® building owner's package, split heat pump for buildings without basements	Outer diameter of cable [mm]	Outer diameter of pipe [inches]	Article number
Incl. 10 m bend-resistant jacket pipe	2 x 6-15	1/4 + 1/2	2040 100 028 91
Incl. 10 m bend-resistant jacket pipe	2 x 6-15	3/8 + 5/8	2040 100 027 91
Incl. 10 m bend-resistant jacket pipe	2 x 6-15	1/4 + 5/8	2040 100 029 91

Prices do not include fixtures and pipes/cables.

inch	Outer diameter
1/4	6,4 mm
1/2	12,7 mm
3/8	9,5 mm
5/8	15,9 mm