

UGA GPD with interchangeable insert



Rubber press seal



PRESSING WATER

- Installation in preinstalled pipe sleeve or core bore in waterproof concrete (white tank)
- Hinged version, for pipes and cables that are already installed
- With replaceable interchangeable insert



PRODUCT ADVANTAGES

- Custom-made for your application
- For retrofitting around existing pipes and cables
- Quick installation
- Interchangeable insert with collar for a secure hold in the rubber press seal
- The split interchangeable insert inside can be replaced with a new one without the entire component having to be removed

TECHNICAL DETAILS

- Certified under FHRK test regulation GE 101 (no. G 30 322-7-2) – FHRK 60 D10
- All metal parts made of stainless steel 1.4301 (V2A), optionally also stainless steel 1.4571/1.4404 (V4A)
- Split version
- Leak-tight against gas and pressing water
- Can accommodate slight axial movements

PRODUCT SCOPE

- Rubber press seal 60 mm (gasket insert) made of EPDM
- Interchangeable insert 60 mm with collar (except WE 125) made of EPDM

The UGA range is excluded from the DOYMA 25-year warranty.



www.doyma.com

GPD with interchangeable insert

Article	Examples for max. utilisation*
GPD100/G/60/WE65/V2A/EPDM (Z)x(D)	$3 \times \emptyset 22$ or $5 \times \emptyset 17$ or $9 \times \emptyset 12$
GPD125/G/60/WE85/V2A/EPDM (Z)x(D)	$3 \times \emptyset 30$ or $5 \times \emptyset 24$ or $9 \times \emptyset 16$
GPD150/G/60/WE110/V2A/EPDM (Z)x(D)	$3 \times \emptyset 42$ or $5 \times \emptyset 34$ or $9 \times \emptyset 24$
GPD200/G/60/WE125/V2A/EPDM (Z)x(D)	$3 \times \emptyset 50$ or $5 \times \emptyset 38$ or $9 \times \emptyset 27$

* Other combinations with different diameters are also possible.

Individual interchangeable insert (optional)

Article
WE65/G/60/EPDM (Z)x(D)
WE85/G/60/EPDM (Z)x(D)
WE110/G/60/EPDM (Z)x(D)
WE125/G/60/EPDM (Z)x(D)