


# UGA GPD with onion ring insert

## Rubber press seal



- Installation in preinstalled pipe sleeve or core bore in waterproof concrete (white tank)
- Variable sealing of cables or pipes with different diameters
- Hinged version, for pipes and cables that are already installed
- With replaceable onion ring inserts



## PRODUCT ADVANTAGES

- Easy installation by separating GPD base and onion ring inserts
- Onion ring inserts can be adapted to the piping on site
- Slip-through protection in the form of two step tabs
- Onion ring inserts in certain sizes can be replaced by interchangeable inserts upon request
- Reserve openings sealed with supplied plugs

## TECHNICAL DETAILS

- All metal parts made of stainless steel 1.4301 (V2A), optionally also stainless steel 1.4571/1.4404 (V4A)
- Gas and watertight
- Split version
- Feed-through of up to 10 cables of different diameters possible

## PRODUCT SCOPE

- Rubber press seal 40 mm (gasket insert) made of EPDM
- Onion ring insert 40 mm with collar made of EPDM

The UGA range is excluded from the DOYMA 25-year warranty.



## GPD with onion ring insert

Inner diameter of pipe sleeve/ core bore	Article	Outer diameter of pipe/cable	Article number
80	GPD80/G/40/ZS/V2A/EPDM 1x(4-32)	1 × (4-32)	4 88 8 001 080 2 4
	GPD80/G/40/ZS/V2A/EPDM 2x(4-25)	2 × (4-25)	4 88 8 002 080 2 4
	GPD80/G/40/ZS/V2A/EPDM 3x(4-20)	3 × (4-20)	4 88 8 003 080 2 4
100	GPD100/G/40/ZS/V2A/EPDM 1x(22-54)	1 × (22-54)	4 88 8 001 100 2 4
	GPD100/G/40/ZS/V2A/EPDM 2x(4-32) + 2x(4-25)	2 × (4-32) + 2 × (4-25)	4 88 8 002 100 2 4
	GPD100/G/40/ZS/V2A/EPDM 2x(4-32) + 3x(4-20)	2 × (4-32) + 3 × (4-20)	4 88 8 003 100 2 4
	GPD100/G/40/ZS/V2A/EPDM 3x(4-32)	3 × (4-32)	4 88 8 004 100 2 4
	GPD100/G/40/ZS/V2A/EPDM 8x(4-20)	8 × (4-20)	4 88 8 005 100 2 4
125	GPD125/G/40/ZS/V2A/EPDM 1x(22-54)	1 × (22-54)	4 88 8 001 125 2 4
	GPD125/G/40/ZS/V2A/EPDM 3x(4-32)	3 × (4-32)	4 88 8 002 125 2 4
	GPD125/G/40/ZS/V2A/EPDM 6x(4-25)	6 × (4-25)	4 88 8 003 125 2 4
	GPD125/G/40/ZS/V2A/EPDM 10x(4-20)	10 × (4-20)	4 88 8 004 125 2 4
150	GPD150/G/40/ZS/V2A/EPDM 3x(22-54)	3 × (22-54)	4 88 8 001 150 2 4
	GPD150/G/40/ZS/V2A/EPDM 4x(4-32) + 6x(4-20)	4 × (4-32) + 6 × (4-20)	4 88 8 002 150 2 4
	GPD150/G/40/ZS/V2A/EPDM 6x(4-32)	6 × (4-32)	4 88 8 003 150 2 4
	GPD150/G/40/ZS/V2A/EPDM 9x(4-25)	9 × (4-25)	4 88 8 004 150 2 4
160	GPD160/G/40/ZS/V2A/EPDM 3x(22-54)	3 × (22-54)	4 88 8 001 160 2 4
	GPD160/G/40/ZS/V2A/EPDM 4x(4-32) + 6x(4-20)	4 × (4-32) + 6 × (4-20)	4 88 8 002 160 2 4
	GPD160/G/40/ZS/V2A/EPDM 6x(4-32)	6 × (4-32)	4 88 8 003 160 2 4
	GPD160/G/40/ZS/V2A/EPDM 9x(4-25)	9 × (4-25)	4 88 8 004 160 2 4
200	GPD200/G/40/ZS/V2A/EPDM 3x(22-54) + 4x(4-25) + 3 × (4-20)	3 × (22-54) + 4 × (4-25) + 3 × (4-20)	4 88 8 001 200 2 4

## Individual onion ring inserts (optional)

Article	Outer diameter of pipe/cable	Article number
ZS/G/40/EPDM 4-20	4-20	4 99 8 001 000 0 4
ZS/G/40/EPDM 4-25	4-25	4 99 8 002 000 0 4
ZS/G/40/EPDM 4-32	4-32	4 99 8 003 000 0 4
ZS/G/40/EPDM 22-54	22-54	4 99 8 004 000 0 4