

# UGA KD 110 system cover

Conical system insert

💧💧 PRESSING WATER

- Use in existing flange sleeves on the connection side
- With screw closure



## PRODUCT ADVANTAGES

- Conical system insert for sealing cables and cable protection pipes
- Easy installation
- Custom-made for your application
- Split version for installing after cables have been laid

The UGA range is excluded from the DOYMA 25-year warranty.



[www.doyma.com](http://www.doyma.com)

I-MT-8-102-01/2024

Subject to technical changes. Some illustrations include accessories.

Article	Outer diameter of pipe/cable	Article number
KD110-D-DGM110	110 mm	4 11 2 110 110 0 4
KD110-E-WE/EPDM (Z) × (D)	1 to 28 bores	—

#### Allocation table for WA conical system insert

Article	Number of bores	D max. outer diameter*
KD110-E-WE/EPDM 1 × (D)	1 bore	up to 110 mm
KD110-E-WE/EPDM 3 × (D)	3 bores	up to 48 mm
KD110-E-WE/EPDM 5 × (D)	5 bores	up to 36 mm
KD110-E-WE/EPDM 7 × (D)	7 bores	up to 32 mm
KD110-E-WE/EPDM 9 × (D)	9 bores	up to 26 mm
KD110-E-WE/EPDM 13 × (D)	13 bores	up to 21 mm
KD110-E-WE/EPDM 19 × (D)	19 bores	up to 18 mm
KD110-E-WE/EPDM 28 × (D)	28 bores	up to 14 mm

\* Other combinations with different diameters are also possible.