


Quadro-Sicura® Nova 2-FW

for building with basements

 PRESSING WATER

- Multi-compartment house lead-in **with sealing on both sides**
- Installation in **pre-installed pipe sleeve or core bore in waterproof concrete (white tank)**
- For the following utilities: district/geothermal heating, water, electricity and telecommunications



25 years
guarantee

PRODUCT ADVANTAGES

- Infinitely variable modular gaskets for water and energy
- Space-saving building lead-in of supply lines
- Easy assignment of utility seal through symbol identification
- Installation without torque spanner possible

TECHNICAL DETAILS

- Dry installation
- Leak-tight against gas and pressing water
- Split sealing of the respective building services
- Variable arrangement of individual compartments possible
- No additional outer seal required
- Connection option for rigid or flexible jacket pipes DN 75 and DN 125. Larger or smaller dimensions are possible via expansion sleeves or reductions
- Visual indication of the tightening torque via control pins

Supply lines	Pipe/cable Ø
Local/district heating or Geothermal heating	Outer diameter 75 mm, 90 mm, 110 mm; optionally 125 mm Outer diameter 32 mm, 40 mm, 50 mm Please specify the diameter with your order
Water	Outer diameter 32 mm, 40 mm, 50 mm; optional outer diameter 63 mm
Electricity	Outer diameter of 26–36 mm; optional outer diameter 36–47 mm
Telecommunications	Outer diameter: 2 × 5–7 mm, 3 × 7–13 mm, 1 × 14–18 mm and 1 × 19–22 mm

Dimensions	
Core bore/pipe sleeve Ø	298–304 mm
Wall thicknesses	200–550 mm

Further dimensions and versions available upon request.

Optional diameters	Article number
2 × 75, 90 or 110 mm	2320 075 000 00
2 × 32–50 mm	Please specify the diameter with your order

Prices do not include fixtures and pipes/cables.



Variant: Quadro-Sicura® Nova 2-FW/
breit for twin/element walls