

HKD DOMO-DW-B

PRESSING WATER

- Installation in **pre-installed pipe sleeve** or **core bore in waterproof concrete** (white tank)



The HKD DOMO-DW-B features robust craftsmanship quality.
Supplied as a plug seal for safe sealing of an opening.

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-6) – FHRK 40 LD10
- Water-tight against pressing water (40 mm seal width)
- Radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material is solid EPDM rubber, optionally NBR
- Gas-tight



ACCESSORIES

- Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.

HKD DOMO-DW-B

Inner diameter of pipe sleeve/core bore [DN in mm]	V2A Article number	V4A Article number
80 (79 – 83)	8 03 0 000 080 2 0	8 03 0 000 080 4 0
100 (99 – 103)	8 03 0 000 100 2 0	8 03 0 000 100 4 0
125 (124 – 128)	8 03 0 000 125 2 0	8 03 0 000 125 4 0
150 (149 – 153)	8 03 0 000 150 2 0	8 03 0 000 150 4 0
200 (199 – 204)	8 03 0 000 200 2 0	8 03 0 000 200 4 0
250 (247 – 253)	8 03 0 000 250 2 0	8 03 0 000 250 4 0
300 (297 – 304)	8 03 0 000 300 2 0	8 03 0 000 300 4 0
350 (347 – 353)	8 03 0 000 350 2 0	8 03 0 000 350 4 0
400 (397 – 403)	8 03 0 000 400 2 0	8 03 0 000 400 4 0
450 (447 – 453)	8 03 0 000 450 2 0	8 03 0 000 450 4 0
500 (497 – 503)	8 03 0 000 500 2 0	8 03 0 000 500 4 0
600 (597 – 603)	8 03 0 000 600 2 0	8 03 0 000 600 4 0

All of the special seals deviating from the standard are delivered as type HKD DISO with 40 mm EPDM elastomer, with 2 × 40 mm EPDM elastomer for DN 800 and higher, for pressing and non-pressing water, and in stainless steel 1.4301 (V2A / Inox 304). The HKD DISO is optionally also available in stainless steel 1.4571 (V4A / Inox 316) and with other elastomer compounds, such as NBR.