

HKD DOMO-DW-M

PRESSING WATER

- Installation in **pre-installed pipe sleeve** or **core bore in waterproof concrete** (white tank)



The HKD DOMO-DW-M features robust craftsmanship quality.
For sealing multiple pipes and cables in one opening.

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-6) – FHRK 40 LD10
- Water-tight against pressing water (40 mm seal width)
- Radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material is solid EPDM rubber, optionally NBR
- Gas-tight



ACCESSORIES

- Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.

HKD DOMO-DW-M

Inner diameter of pipe sleeve/core bore [DN in mm]	Outer diameter of pipe/cable [mm]	Number of pipes or cables
80 (79 – 83)	5 – 25 / 5 – 15	1 – 2 / 1 – 2
	5 – 15	1 – 7
100 (99 – 103)	10 – 35 / 5 – 20	1 – 2 / 1 – 2
	5 – 25	1 – 4
	10 – 50 / 5 – 20	1 / 1
	10 – 40 / 5 – 20	1 / 1 – 2
	5 – 20	1 – 7
125 (124 – 128)	10 – 40 / 5 – 30	1 – 2 / 1 – 2
	10 – 35	1 – 4
	5 – 25	1 – 7
150 (149 – 153)	10 – 50 / 10 – 35	1 – 2 / 1 – 2
	10 – 30	1 – 7
	10 – 50	1 – 3
200 (199 – 204)	10 – 50 / 5 – 20	1 – 3 / 1 – 4
	10 – 50	1 – 5
	40 – 65	1 – 4

No article numbers. Precise outer diameter and number of pipes and cables must be specified in your order.

All of the special seals deviating from the standard are delivered as type HKD DISO with 40 mm EPDM elastomer, with 2 × 40 mm EPDM elastomer for DN 800 and higher, for pressing and non-pressing water, and in stainless steel 1.4301 (V2A / Inox 304). The HKD DISO is optionally also available in a split version for pipes and cables that are already installed, in stainless steel 1.4571 (V4A / Inox 316) and with other elastomer compounds, such as NBR.