




# HKD DOMO-DW-NK

 PRESSING WATER

- Installation in **pre-installed pipe sleeve** or **core bore in waterproof concrete** (white tank)



The HKD DOMO-DW-NK features robust craftsmanship quality. **For gentle sealing of plastic jacket pipes, cable protection pipes and flexible pre-insulated plastic pipes. Can also be used for twin/element walls.**

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-6) – FHRK 80 LD10
- Water-tight against pressing water (80 mm seal width)
- radon proof – according to FHRK information sheet MB101
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material is solid EPDM rubber, extra soft
- Gas-tight



## ACCESSORIES

- Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.



## HKD DOMO-DW-NK

Inner diameter of pipe sleeve/core bore [DN in mm]	Outer diameter of pipe/cable d [mm]	V2A Article number	V4A Article number	
80 (79 – 83)	11 – 13	8 03 4 012 080 2 0	8 03 4 012 080 4 0	
	14 – 16	8 03 4 015 080 2 0	8 03 4 015 080 4 0	
	17 – 19	8 03 4 017 080 2 0	8 03 4 017 080 4 0	
	20 – 22	8 03 4 022 080 2 0	8 03 4 022 080 4 0	
	25 – 27	8 03 4 025 080 2 0	8 03 4 025 080 4 0	
	28 – 31	8 03 4 028 080 2 0	8 03 4 028 080 4 0	
	32 – 35	8 03 4 032 080 2 0	8 03 4 032 080 4 0	
	36 – 40	8 03 4 040 080 2 0	8 03 4 040 080 4 0	
100 (99 – 103)	12 – 16	8 03 4 015 100 2 0	8 03 4 015 100 4 0	
	17 – 21	8 03 4 020 100 2 0	8 03 4 020 100 4 0	
	22 – 26	8 03 4 025 100 2 0	8 03 4 025 100 4 0	
	27 – 31	8 03 4 028 100 2 0	8 03 4 028 100 4 0	
	32 – 35	8 03 4 032 100 2 0	8 03 4 032 100 4 0	
	36 – 40	8 03 4 040 100 2 0	8 03 4 040 100 4 0	
	41 – 44	8 03 4 042 100 2 0	8 03 4 042 100 4 0	
	48 – 51	8 03 4 050 100 2 0	8 03 4 050 100 4 0	
	52 – 54	8 03 4 054 100 2 0	8 03 4 054 100 4 0	
	55 – 56	8 03 4 056 100 2 0	8 03 4 056 100 4 0	
	57 – 57	8 03 4 057 100 2 0	8 03 4 057 100 4 0	
	58 – 58	8 03 4 058 100 2 0	8 03 4 058 100 4 0	
125 (124 – 128)	60 – 60	8 03 4 060 100 2 0	8 03 4 060 100 4 0	
	63 – 63	8 03 4 063 100 2 0	8 03 4 063 100 4 0	
	57 – 61	8 03 4 060 125 2 0	8 03 4 060 125 4 0	
	62 – 64	8 03 4 063 125 2 0	8 03 4 063 125 4 0	
	73 – 75	8 03 4 075 125 2 0	8 03 4 075 125 4 0	
	76 – 77	8 03 4 076 125 2 0	8 03 4 076 125 4 0	
	150 (149 – 153)	57 – 60	8 03 4 060 150 2 0	8 03 4 060 150 4 0
		74 – 77	8 03 4 075 150 2 0	8 03 4 075 150 4 0
78 – 80		8 03 4 078 150 2 0	8 03 4 078 150 4 0	
88 – 91		8 03 4 090 150 2 0	8 03 4 090 150 4 0	
98 – 100		8 03 4 098 150 2 0	8 03 4 098 150 4 0	
101 – 104		8 03 4 102 150 2 0	8 03 4 102 150 4 0	
108 – 110		8 03 4 110 150 2 0	8 03 4 110 150 4 0	
111 – 115		8 03 4 114 150 2 0	8 03 4 114 150 4 0	
200 (199 – 204)	108 – 112	8 03 4 110 200 2 0	8 03 4 110 200 4 0	
	113 – 115	8 03 4 114 200 2 0	8 03 4 114 200 4 0	
	116 – 118	8 03 4 118 200 2 0	8 03 4 118 200 4 0	
	123 – 126	8 03 4 125 200 2 0	8 03 4 125 200 4 0	
	133 – 136	8 03 4 135 200 2 0	8 03 4 135 200 4 0	
	137 – 141	8 03 4 140 200 2 0	8 03 4 140 200 4 0	
	142 – 145	8 03 4 144 200 2 0	8 03 4 144 200 4 0	
	159 – 160	8 03 4 160 200 2 0	8 03 4 160 200 4 0	

Inner diameter of pipe sleeve/core bore [DN in mm]	Outer diameter of pipe/cable d [mm]	V2A Article number	V4A Article number
250 (247 – 253)	137 – 141	8 03 4 140 250 2 0	8 03 4 140 250 4 0
	142 – 144	8 03 4 144 250 2 0	8 03 4 144 250 4 0
	148 – 152	8 03 4 148 250 2 0	8 03 4 148 250 4 0
	158 – 162	8 03 4 160 250 2 0	8 03 4 160 250 4 0
	168 – 170	8 03 4 170 250 2 0	8 03 4 170 250 4 0
	174 – 177	8 03 4 175 250 2 0	8 03 4 175 250 4 0
	178 – 181	8 03 4 180 250 2 0	8 03 4 180 250 4 0
	200 – 204	8 03 4 200 300 2 0	8 03 4 200 300 4 0
300 (297 – 304)	209 – 212	8 03 4 210 300 2 0	8 03 4 210 300 4 0
	219 – 223	8 03 4 222 300 2 0	8 03 4 222 300 4 0
	224 – 226	8 03 4 225 300 2 0	8 03 4 225 300 4 0
350 (347 – 353)	240 – 244	8 03 4 242 350 2 0	8 03 4 242 350 4 0
	249 – 253	8 03 4 250 350 2 0	8 03 4 250 350 4 0
	271 – 275	8 03 4 271 350 2 0	8 03 4 271 350 4 0
	278 – 280	8 03 4 280 350 2 0	8 03 4 280 350 4 0
400 (397 – 403)	312 – 316	8 03 4 315 400 2 0	8 03 4 315 400 4 0
	322 – 325	8 03 4 324 400 2 0	8 03 4 324 400 4 0
	326 – 329	8 03 4 326 400 2 0	8 03 4 326 400 4 0
450 (447 – 453)	353 – 356	8 03 4 355 450 2 0	8 03 4 355 450 4 0
500 (497 – 503)	398 – 401	8 03 4 400 500 2 0	8 03 4 400 500 4 0
	406 – 410	8 03 4 406 500 2 0	8 03 4 406 500 4 0
	426 – 430	8 03 4 429 500 2 0	8 03 4 429 500 4 0
600 (597 – 603)	448 – 451	8 03 4 450 600 2 0	8 03 4 450 600 4 0
	498 – 501	8 03 4 500 600 2 0	8 03 4 500 600 4 0
	508 – 510	8 03 4 508 600 2 0	8 03 4 508 600 4 0