



HKD DOMO-V / HKD DOMO-VT



PRESSING WATER

Installation in pre-installed pipe sleeve or core bore in waterproof concrete (white tank)







The HKD DOMO-V models can be variably adjusted to the diameter of the pipe or cable. One HKD DOMO-V type can therefore replace up to 10 standard sizes. The HKD DOMO-VT type is a hinged version for use on pipes and cables that have already been installed. It is adapted to the relevant diameter by simply removing the rubber elements that are not required.

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-6) - FHRK 40 LD10
- Water-tight against pressing water
- Radon-tight-according to FHRK information sheet MB101meets the requirements for radon precautionary areas
- HKD DOMO-VT: hinged version, for pipes and cables that are already installed with pipe sleeve/core bore DN 100
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material: EPDM 40 mm wide
- Gas-tight

 Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.



M-MT-1-904-01/2024

Subject to technical changes. Some illustrations include accessories.

HKD DOMO-V/HKD DOMO-VT

Туре	Inner diameter of pipe sleeve/core bore [DN in mm]	Outer diameter of pipe/cable [mm]	V2A Article number
DOMO-V 100	DN 100 (99 - 102)	0 (blind)	8 88 0 000 100 2 0
		18 – 19	
		20 – 24	
		25 – 29	
		30 – 34	
		35 – 39	
		40 – 44	
		45 – 49	
		50 – 54	
		55 – 59	
		60 – 65	
DOMO-VT 100	DN 100 (99 - 102)	0 (blind)	8 88 2 000 100 2 0
		32	
		40	
		50	
		63	
DOMO-V 150	DN 150 (149 - 152)	O (blind)	8 88 0 000 150 2 0
		62 – 63	
		75 – 77	
		88 – 90	
		108 -110	
DOMO-V 200	DN 200 (199 - 202)	0 (blind)	8 88 0 000 200 2 0
		108 – 110	
		123 – 125	
		133 – 135	
		158 – 160	

V4A upon request.

