

HKD KE pipe sleeve with bonding flange

NON-PRESSING WATER

PRESSING WATER

- Use in **unfinished structures**
- For use with **sealants to be processed in liquid form** (black tank)
- With **bonding flange** in accordance with DIN 18533



- Certified under FHRK test regulation GE 102 (no. G 30 668) – FHRK 40 LD10
- Keyed surface for better connection between the pipe sleeve and concrete roughened surface
- Sealing system on both sides with movable EPDM lip seals
- Bonding flange for the on-site application of a thick coating (PMBC/KMB) with pressing water (W2.1-E)
- Bonding flange for the on-site application of a mineral sealing slurry (MDS) or a liquid plastic (FLK) with non-pressing water (W1-E or W3-E)
- Radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- The inner diameter matches the nominal diameter DN
- High dimensional stability
- Lightweight, impact-resistant plastic
- Gas-tight
- Can be used in twin/element walls
- Lengths: 200–500 mm
- Closed on both sides with PE caps



ACCESSORIES

- Formwork fastener (1701), see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.



HKD KE pipe sleeve with bonding flange

Nominal size [DN in mm]	Outer diameter of bonding flange max. [mm]	Length [mm]	Article number
80	192	200	8 10 0 080 200 0 9
		240	8 10 0 080 240 0 9
		250	8 10 0 080 250 0 9
		300	8 10 0 080 300 0 9
		350	8 10 0 080 350 0 9
		365	8 10 0 080 365 0 9
		400	8 10 0 080 400 0 9
		500	8 10 0 080 500 0 9
100	212	200	8 10 0 100 200 0 9
		240	8 10 0 100 240 0 9
		250	8 10 0 100 250 0 9
		300	8 10 0 100 300 0 9
		350	8 10 0 100 350 0 9
		365	8 10 0 100 365 0 9
		400	8 10 0 100 400 0 9
		500	8 10 0 100 500 0 9
125	234	200	8 10 0 125 200 0 9
		240	8 10 0 125 240 0 9
		250	8 10 0 125 250 0 9
		300	8 10 0 125 300 0 9
		350	8 10 0 125 350 0 9
		365	8 10 0 125 365 0 9
		400	8 10 0 125 400 0 9
		500	8 10 0 125 500 0 9
150	262	200	8 10 0 150 200 0 9
		240	8 10 0 150 240 0 9
		250	8 10 0 150 250 0 9
		300	8 10 0 150 300 0 9
		350	8 10 0 150 350 0 9
		365	8 10 0 150 365 0 9
		400	8 10 0 150 400 0 9
		500	8 10 0 150 500 0 9
200	312	200	8 10 0 200 200 0 9
		240	8 10 0 200 240 0 9
		250	8 10 0 200 250 0 9
		300	8 10 0 200 300 0 9
		350	8 10 0 200 350 0 9
		365	8 10 0 200 365 0 9
		400	8 10 0 200 400 0 9
		500	8 10 0 200 500 0 9

Further types and sizes of casings can be found in the Curaflex product range
(see notes on combination of the HKD and DOYMA product range).