



# HKD KG 2000 sewer floor element



- Use in **unfinished floor slabs to be made of waterproof concrete** (white tank)



APP-PU 50



- KG 2000 sewer pipe as sleeve with seal element made of EPDM
- Water-tight against gas and pressing water upon installation in the floor slab
- Radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- KG 2000 sewer pipes in accordance with DIN EN 14758
- Polypropylene solid-walled pipe; more impact-resistant and more abrasion-resistant than KG
- Length approx. 500 mm
- Optionally also available with foil flange for connecting moisture barriers in the form of tanking membranes

## Without foil flange

Nominal size [DN in mm]	Article number
100	8 20 1 100 500 1 0
125	8 20 1 125 500 1 0
150	8 20 1 150 500 1 0
200	8 20 1 200 500 1 0

## With foil flange

Nominal size [DN in mm]	Article number
100	8 20 1 100 500 1 1
125	8 20 1 125 500 1 1
150	8 20 1 150 500 1 1
200	8 20 1 200 500 1 1

## OPTIONAL ACCESSORIES

APP-PU 50	Article number
Accessories for foil flanges	8 99 0 050 000 0 0

Further information can be found on the HKD APP-PU 50 product page.



### ACCESSORIES

- One-component polyurethane sealant material APP-PU 50 with a very good adhesion to steel, plastics and concrete.

The HKD range is excluded from the DOYMA 25-year warranty.

