

HKD KG 2000 sewer plug-in flange

NON-PRESSING WATER

- Renovation type for retrofitting in existing KG 2000 sewer wall elements in walls with tanking membranes or thick coatings (black tank)



APP-PU 50



- KG sewer plug-in flange for subsequent sealing of already cast-in KG sewer wall elements for sealing with tanking membranes or thick coatings
- With moulded plug-in sleeve on one side and with foil flange for connecting moisture barriers in the form of tanking membranes; diameter of foil flange 430–520 mm.
- radon proof – according to FHRK information sheet MB101
- KG 2000 sewer pipes in accordance with DIN EN 14758

Nominal size [DN in mm]	Plug-in depth [mm]	Article number
100	65	8 20 0 100 000 1 3
125	75	8 20 0 125 000 1 3
150	85	8 20 0 150 000 1 3
200	95	8 20 0 200 000 1 3

OPTIONAL ACCESSORIES

APP-PU 50	Article number
Accessories for foil flanges	8 99 0 050 000 0 0

Further information can be found on the HKD APP-PU 50 product page.



ACCESSORIES

- One-component polyurethane sealant material APP-PU 50 with a very good adhesion to steel, plastics and concrete.

The HKD range is excluded from the DOYMA 25-year warranty.

