



HKD KG 2000 sewer wall element



- Use in unfinished walls to be made of waterproof concrete (white tank)



- KG 2000 sewer pipe as double sleeve with seal element made of EPDM
- Water-tight against gas and pressing water upon installation in a white tank wall
- Radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- KG 2000 sewer pipes in accordance with DIN EN 14758
- Polypropylene solid-walled pipe; more impact-resistant and more abrasion-resistant than KG
- For wall thicknesses of 200–500 mm
- Including installation aids/cap

| Nominal size [DN in mm] | Length [mm] | Article number |
|-------------------------|-------------|--------------------|
| 100 | 200 | 8 20 0 100 200 1 0 |
| | 240 | 8 20 0 100 240 1 0 |
| | 250 | 8 20 0 100 250 1 0 |
| | 300 | 8 20 0 100 300 1 0 |
| | 350 | 8 20 0 100 350 1 0 |
| | 365 | 8 20 0 100 365 1 0 |
| | 400 | 8 200 100 400 1 0 |
| 125 | 200 | 8 20 0 125 200 1 0 |
| | 240 | 8 20 0 125 240 1 0 |
| | 250 | 8 20 0 125 250 1 0 |
| | 300 | 8 20 0 125 300 1 0 |
| | 350 | 8 20 0 125 350 1 0 |
| | 365 | 8 20 0 125 365 1 0 |
| | 400 | 8 20 0 125 400 1 0 |
| 150 | 200 | 8 20 0 150 200 1 0 |
| | 240 | 8 20 0 150 240 1 0 |
| | 250 | 8 20 0 150 250 1 0 |
| | 300 | 8 20 0 150 300 1 0 |
| | 350 | 8 20 0 150 350 1 0 |
| | 365 | 8 20 0 150 365 1 0 |
| | 400 | 8 20 0 150 400 1 0 |
| 200 | 240 | 8 20 0 200 240 1 0 |
| | 250 | 8 20 0 200 250 1 0 |
| | 300 | 8 20 0 200 300 1 0 |
| | 350 | 8 20 0 200 350 1 0 |
| | 365 | 8 20 0 200 365 1 0 |
| | 400 | 8 20 0 200 400 1 0 |
| | 500 | 8 20 0 200 500 1 0 |

The HKD range is excluded from the DOYMA 25-year warranty.