


HKD connection funnel



- Use in **unfinished floor slabs to be made of waterproof concrete** (white tank)
- Moisture barrier connection via bonding flange in accordance with DIN 18533 W1-E



- Connection funnel made of ABS for embedding in the floor slab to create the optimal seal for KG sewer pipe with outer diameter 110 mm
- Allows for correction of a misalignment (after embedding in concrete) between the downpipe and building drain connection in any direction
- Replaces square cut-outs and therefore the additional subsequent work (concrete pouring)
- With integrated level for positional alignment of the connection funnel
- Integrated impact-protection insert made of PP to ensure trip-proof installation in accordance with DGUV 38 §12a
- Gas and watertight connection with the floor slab thanks to integrated 3-strip seal made of TPE
- radon proof – according to FHRK information sheet MB101
- Safe sealing for pre-installed KG sewer pipe through TPE sealing lips
- Connection funnel can be used for floor slab drainage during the building phase
- With protective film applied (including installation notes) to ensure function during the raw construction phase

Nominal size [DN in mm]	Outer diameter of bonding flang [mm]	PU	Article number
110	385	1 Item	8 00 1 000 001 0 0
		3 Items	8 00 1 000 003 0 0
		6 Items	8 00 1 000 006 0 0
		1 Item *	8 00 1 000 001 0 1

* Individually packed per item.



Protective film