

Link-Seal C, S316

Link chains for steel/cast iron pipes

PRESSING WATER

- Sealing of duct systems
- Installation in **pre-installed pipe sleeve** or **core bore in waterproof concrete** (white tank)
- **Split version**, for **pipes and cables that are already installed**



PRODUCT ADVANTAGES

- Quick installation thanks to pre-assembled system
- Robust rubber parts ensure a long service life
- The radial expansion of the rubber parts ensures a permanent, pressure-tight and secure sealing of the annular space
- Oil, fuel and solvent-resistant or high-temperature resistant versions and versions with KTW approval are available
- Easy installation; even retrofitting possible

TECHNICAL DETAILS


- Certified under FHRK test regulation GE 101 (no. G 30 322-6-2)
- Water-tight against pressing water
- radon proof – according to FHRK information sheet MB101
- For galvanised screws: general application in normal atmosphere, water or humidity. Suitable for electrical insulation and cathodic corrosion protection
- For stainless steel screws: high resistance to water, against most inorganic substances (acids and alkalis) and most organic substances (e.g. acetic acid and acetone)
- LS 200 to LS 275 FHRK standard 20, 30, 40
- LS 300 to LS 700 FHRK standard 20, 30, 40, 60

MATERIAL

- Pressure plates: glass fibre reinforced polyamide
- Rubber material: black EPDM rubber
- Version C: galvanised steel screws
- Version S316: A4-70 stainless steel screws



Individual module



The HKD range is excluded from the DOYMA 25-year warranty.

Link-Seal C (galvanised steel screws)

Module type/ quantity	Inner diameter [DN in mm]	Outer diameter d [mm]	Article number
LS200	–	–	6 50 0 200 000 0 0
LS265	–	–	6 50 0 265 000 0 0
LS275	–	–	6 50 0 275 000 0 0
LS300	–	–	6 50 0 300 000 0 0
LS310	–	–	6 50 0 310 000 0 0
LS315	–	–	6 50 0 315 000 0 0
LS325	–	–	6 50 0 325 000 0 0
LS340	–	–	6 50 0 340 000 0 0
LS360	–	–	6 50 0 360 000 0 0
LS400	–	–	6 50 0 400 000 0 0
LS410	–	–	6 50 0 410 000 0 0
LS425	–	–	6 50 0 425 000 0 0
LS440	–	–	6 50 0 440 000 0 0
LS475	–	–	6 50 0 475 000 0 0
LS500	–	–	6 50 0 500 000 0 0
LS525	–	–	6 50 0 525 000 0 0
LS575	–	–	6 50 0 575 000 0 0
LS615	–	–	6 50 0 615 000 0 0
LS650	–	–	6 50 0 650 000 0 0
6x315	100	48	6 50 0 048 100 0 0
6x300	100	58 + 60	6 50 0 060 100 0 0
5x360	125	42 + 48	6 50 0 048 125 0 0
7x340	125	60	6 50 0 060 125 0 0
8x315	125	76	6 50 0 076 125 0 0
5x410	150	58 + 60	6 50 0 060 150 0 0
9x340	150	89	6 50 0 089 150 0 0
10x315	150	98	6 50 0 098 150 0 0
7x310	150	110	6 50 0 110 150 0 0
10x265	150	114	6 50 0 114 150 0 0
7x475	200	110	6 50 0 110 200 0 0
7x410	200	114	6 50 0 114 200 0 0
13x340	200	135	6 50 0 135 200 0 0
7x400	250	168	6 50 0 168 250 0 0
7x500	300	160 + 168 + 170	6 50 0 160 300 0 0
12x410	300	210 + 219	6 50 0 219 300 0 0
15x360	300	222	6 50 0 222 300 0 0
18x360	350	273	6 50 0 273 350 0 0

Further material combinations available upon request.

Link-Seal S316 (A4-70 stainless steel screws)

Module type/ quantity	Inner diameter [DN in mm]	Outer diameter d [mm]	Article number
LS200	–	–	6 50 0 200 000 4 0
LS265	–	–	6 50 0 265 000 4 0
LS275	–	–	6 50 0 275 000 4 0
LS300	–	–	6 50 0 300 000 4 0
LS310	–	–	6 50 0 310 000 4 0
LS315	–	–	6 50 0 315 000 4 0
LS325	–	–	6 50 0 325 000 4 0
LS340	–	–	6 50 0 340 000 4 0
LS360	–	–	6 50 0 360 000 4 0
LS400	–	–	6 50 0 400 000 4 0
LS410	–	–	6 50 0 410 000 4 0
LS425	–	–	6 50 0 425 000 4 0
LS440	–	–	6 50 0 440 000 4 0
LS475	–	–	6 50 0 475 000 4 0
LS500	–	–	6 50 0 500 000 4 0
LS525	–	–	6 50 0 525 000 4 0
LS575	–	–	6 50 0 575 000 4 0
LS615	–	–	6 50 0 615 000 4 0
LS650	–	–	6 50 0 650 000 4 0
6x315	100	48	6 50 0 048 100 4 0
6x300	100	58 + 60	6 50 0 060 100 4 0
5x360	125	42 + 48	6 50 0 048 125 4 0
7x340	125	60	6 50 0 060 125 4 0
8x315	125	76	6 50 0 076 125 4 0
5x410	150	58 + 60	6 50 0 060 150 4 0
9x340	150	89	6 50 0 089 150 4 0
10x315	150	98	6 50 0 098 150 4 0
7x310	150	110	6 50 0 110 150 4 0
10x265	150	114	6 50 0 114 150 4 0
7x475	200	110	6 50 0 110 200 4 0
7x410	200	114	6 50 0 114 200 4 0
13x340	200	135	6 50 0 135 200 4 0
7x400	250	168	6 50 0 168 250 4 0
7x500	300	160 + 168 + 170	6 50 0 160 300 4 0
12x410	300	210 + 219	6 50 0 219 300 4 0
15x360	300	222	6 50 0 222 300 4 0
18x360	350	273	6 50 0 273 350 4 0