



HKD KG 2000 sewer floor element

 PRESSING WATER

- Use in unfinished floor slabs to be made of waterproof concrete (white tank)



- KG 2000 sewer pipe as sleeve with seal element made of EPDM
- Water-tight against gas and pressing water upon installation in the floor slab
- Radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- KG 2000 sewer pipes in accordance with DIN EN 14758
- Polypropylene solid-walled pipe; more impact-resistant and more abrasion-resistant than KG
- Length approx. 500 mm
- Optionally also available with foil flange for connecting moisture barriers in the form of tanking membranes

Without foil flange

Nominal size [DN in mm]	Article number
100	8 20 1 100 500 1 0
125	8 20 1 125 500 1 0
150	8 20 1 150 500 1 0
200	8 20 1 200 500 1 0

With foil flange

Nominal size [DN in mm]	Foil flange-OD D _A [mm]	Article number
100	430	8 20 1 100 500 1 1
125	470	8 20 1 125 500 1 1
150	490	8 20 1 150 500 1 1
200	520	8 20 1 200 500 1 1

OPTIONAL ACCESSORIES

Sikaflex-11 FC Purform	Article number
Accessories for foil flanges	1 99 0 756 000 0 0

Further information can be found on the Sikaflex-11 FC Purform product page.

ACCESSORIES

- One-component polyurethane sealant material Sikaflex-11 FC Purform with a very good adhesion to steel, plastics and concrete.

The HKD range is excluded from the DOYMA 25-year warranty.

