

HKD KG sewer plug-in flange

NON-PRESSING WATER

- Renovation type for retrofitting in existing KG sewer wall elements in walls with tanking membranes or thick coatings (black tank)



- KG sewer plug-in flange for subsequent sealing of already cast-in KG sewer wall elements for sealing with tanking membranes or thick coatings
- With moulded plug-in sleeve on one side and with foil flange for connecting moisture barriers in the form of tanking membranes.
- radon proof – according to FHRK information sheet MB101
- KG sewer pipes in accordance with DIN EN 13476-2

Nominal size [DN in mm]	Plug-in depth [mm]	Foil flange-OD D _A [mm]	Article number
100	65	430	8 20 0 100 000 0 3
125	75	470	8 20 0 125 000 0 3
150	85	490	8 20 0 150 000 0 3
200	95	520	8 20 0 200 000 0 3

OPTIONAL ACCESSORIES

Sikaflex-11 FC Purform	Article number
Accessories for foil flanges	1 99 0 756 000 0 0

Further information can be found on the Sikaflex-11 FC Purform product page.



ACCESSORIES

- One-component polyurethane sealant material Sikaflex-11 FC Purform with a very good adhesion to steel, plastics and concrete.

The HKD range is excluded from the DOYMA 25-year warranty.

