


Quadro-Sicura® ADS

for buildings without basements

 PRESSING WATER

- Single-compartment house lead-in as a **round version**
- Use in **unfinished structures made of waterproof concrete**
- For utilities **gas or water**
- House lead-ins with **larger dimensions**



Quadro-Sicura®
ADS gas

Quadro-Sicura®
ADS water

PRODUCT ADVANTAGES

- Bend-resistant jacket pipes for compliance with bending radii
- Subsequent replacement of pipes and cables possible (relining)

TECHNICAL DETAILS

- Leak-tight against gas and pressing water
- radon proof – according to FHRK information sheet MB101
- Suitable for immediate installation in the floor slab or for later retrofitting in a cut-out in the floor slab
- One installation part, consisting of Schuck house lead-ins combination including tear-off protection and anti-twist protection, as well as pre-assembled gasket inserts
- Cast-in part consisting of plastic pipe sleeve and one connecting sleeve including integrated bend-resistant jacket pipe and height-adjustable rod

Type/version	House lead-in combination [DN]	Plastic pipe sleeve [DN]	Inner diameter Jacket pipe [mm]
Quadro-Sicura® ADS gas/water	50	100	110
Quadro-Sicura® ADS gas/water	80	150	150

Further dimensions and versions available upon request.

DN of house lead-in combination
50
80

Equipped with 3 m bend-resistant jacket pipe.

The Quadro-Sicura ADS system is excluded from the DOYMA 25-year warranty.

