for buildings without basements

- 444
 - PRESSING WATER
- Single-compartment house lead-in as a round version
- Use in unfinished structures made of waterproof concrete
- House lead-in for sealing flexible pre-insulated local and district heating pipes





PRODUCT ADVANTAGES

- Rigid pipe bend for compliance with bending radii and easy pipe entry
- Pipes and cables can be laid independently from construction progress
- Subsequent replacement of pipes and cables possible (relining)
- Earth-side extension possible with commercially available pipes (plug-in sleeve)

TECHNICAL DETAILS

- Leak-tight against gas and pressing water
- radon proof according to FHRK information sheet MB101
- Suitable for immediate installation in the floor slab or for later retrofitting in a cut-out in the floor slab
- Cast-in part consisting of plastic pipe sleeve and one connecting sleeve including integrated bend-resistant jacket pipe and height-adjustable rod
- Quadro-Secura® E-BP/SRB with nominal diameter 200 for pipes and cables with diameters from 75 to 142 mm
- Quadro-Secura® E-BP/SRB with nominal diameter 250 for pipes and cables with diameters from 141 to 178 mm

Type/version	Plastic pipe sleeve [DN] [ID/mm]		bending radii pipe bend [mm]
Quadro-Secura® E-BP/SRB	200	188	800
Quadro-Secura® E-BP/SRB	250	235	800

The minimum bending radii for the media pipes/cables to be installed must be observed.



- ACCESSORIES NECESSARY
- Curaflex® C40/SRB (see selection table on next page)





Product	Plastic pipe sleeve		Ding/sable @ [mm]	Article number
	DN	ID [mm]	Pipe/cable Ø [mm]	Afficie Hullidei
Quadro-Secura® E-BP/SRB	200	188	75 - 142	2850 000 200 00
	250	235	141 - 178	2850 000 250 00

Product	Plastic pipe sleeve		Pipe/cable Ø [mm]	Article number
	DN	ID [mm]	r ipe/cable & [illili]	Ai litte liollidei
Curaflex® C 40/SRB	200	188	75 - 80	1034 075 188 00
			88 - 93	1034 090 188 00
			109 - 114	1034 110 188 00
			123 - 128	1034 125 188 00
			138 - 142	1034 140 188 00
	250	235	141 - 146	1034 142 235 00
			158 - 163	1034 160 235 00
			173 - 178	1034 175 235 00

Further dimensions and versions available upon request. Additional information about our Curaflex $^{\otimes}$ sealing systems can be found in the applicable product documentation.



Curaflex Nova® C40/SRB