


NEW

Quadro-Sicura® O.Con 1

for buildings without basements

 PRESSING WATER

- Single-compartment house outlet with as round design
- Use in structures yet to be built of WU concrete
- Hausausführung für for all types of cables or water pipes
- Ideal for connections in the garden or outdoors

25
Jahre
Garantie



PRODUCT ADVANTAGES

- Later insertion of pipes for use in garden or outdoor areas. or outdoor areas
- No drilling or the like required on the building for later laying of lines
- Various sealing options for different lines possible
- Quick installation

TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 0,5 bar
- optional installation according to DIN 18533 possible
- suitable for immediate installation in the floor slab or for later installation in a recess in the floor slab floor slab
- connection possibility of flexible casing pipes DN 75
- End plug is pre-fitted with gas- and pressure-water-tight blanking plugs
- optionally available with 3 m, 6 m, 10 m or 15 m flexible outer casing available
- for pipes $\varnothing \geq 40$ mm we recommend the use of Quadro-Sicura® E-BP-R Max.

THE HOUSE LEAD-IN CONSISTS OF:

- Plastic pipe sleeve incl. blind cover
- Connection sleeve for connecting pipe sleeve/casing pipe
- End plug for sealing the pipe

Quadro-Sicura® O.Con 1	Pipe/cable \varnothing [mm]
XLWL end plug	Outer diameter: 2 x 5-7 mm, 2 x 7-13 mm, 1 x 12-16 mm, 1 x 23-40 mm

Further dimensions and designs on request.



ACCESSORIES – RECOMMENDED

- flexible casing pipe DN 75
- height-adjustable installation device
- End plug XLWL for ground-side line-sealing
- Sealing sleeve for connection of a sealing membrane



Product	Plastic pipe sleeve [DN]	Length of jacket pipe DN 75	Article number
Quadro-Secura® O.Con 1	75	-	2285 000 000 00
		3 metre	2285 000 000 03
		6 metre	2285 000 000 06
		10 metre	2285 000 000 01
		15 metre	2285 000 000 05

Accessories

Product	Article number
Height adjustable set-up device (2799)	2990 799 999 00
XLWL end plug for earth-side cable sealing (2704)	2990 704 925 50
Sealing sleeve for connecting a waterproofing membrane to the floor slab (2718)	2990 718 075 00
Flexible casing pipe DN 75, black, 50 metre roll (2775)	2990 775 675 00

Height adjustable
Set-up device
(2799)



XLWL end plug (2704)
for earth-side cable sealing



Sealing sleeve (2718)
for connecting a waterproofing
membrane to the floor slab



Flexible casing pipe DN 75
(2775)

