



# Quadro-Sicura® Quick/G

for buildings with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** or for **core bore in waterproof concrete** (white tank)
- For the utility **gas**
- With seal flange in accordance with **DIN 18533** (black tank)
- Ideal for **new connections** in existing buildings



## PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Allows for the simultaneous routing of gas duct system combinations and fibre optic cables/pipes ( $2 \times \varnothing 7 \text{ mm}$ )
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations
- No additional mechanical fastening required

## TECHNICAL DETAILS

- DVGW-approved (RMA, Schuck und VAF Voigt)
- Leak-tight against gas and pressing water up to 1 bar
- For open design
- Suitable for RMA / Schuck / VAF Voigt / Burger gas duct system combinations
- For bores in the most common wall types with sealing in accordance with DIN 18533 W2.1-E and for core bores in waterproof concrete (white tank)

## THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® Quick/G
- Wall termination ring
- Expansion resin (selectable)



### ACCESSORIES – RECOMMENDED

- 2K cartridge gun



Supply lines	Gas duct system type
Gas	RMA, Schuck, VAF Voigt or Burger

Dimensions	
Core bore/pipe sleeve Ø	99–103 mm
Wall thicknesses	200 – max. 1140 mm (depending on gas duct system type)
Outer diameter of seal flange	200 mm

### Variant including expansion resin

Product	Gas duct system type	Article number	VPE
Quadro-Secura® Quick/G	RMA/Schuck DN 25	2618 025 000 10	1 Stück
	VAF-Voigt DN 25	2613 025 000 10	
	Burger DN 25 + DN 32	2614 025 000 10	
	RMA/Schuck DN 25	2618 025 000 11	10 Stück
	VAF-Voigt DN 25	2613 025 000 11	
	Burger DN 25 + DN 32	2614 025 000 11	

Prices do not include fixtures and pipes.

### Variant excluding expansion resin

Product	Gas duct system type	Article number	VPE
Quadro-Secura® Quick/G	RMA/Schuck DN 25	2618 025 000 00	1 Stück
	VAF-Voigt DN 25	2613 025 000 00	
	Burger DN 25 + DN 32	2614 025 000 00	
	RMA/Schuck DN 25	2618 025 000 01	10 Stück
	VAF-Voigt DN 25	2613 025 000 01	
	Burger DN 25 + DN 32	2614 025 000 01	

Prices do not include fixtures and pipes.

### Dimensions

RMA Gas-HEK overall length	For a wall thicknesses
730 mm	200 - 420 mm
1100 mm	200 - 660 mm
1250 mm	200 - 810 mm
Schuck Gas-HEK overall length	For a wall thicknesses
700 mm	200 - 390 mm
1000 mm	200 - 690 mm
1485 mm	200 - 1140 mm
Burger Gas-HEK overall length	For a wall thicknesses
750 mm	200 - 650 mm
1150 mm	200 - 900 mm
1500 mm	200 - 1140 mm