

Quadro-Sicura® Quick/O

for buildings with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** or for **core bore in waterproof concrete** (white tank)
- For sealing **sewer pipes DN 110**
- With seal flange in accordance with **DIN 18533** (black tank)
- Ideal for **new connections** in existing buildings



PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 1 bar
- For open design
- For bores in the most common wall types with sealing in accordance with DIN 18533 W2.1-E and for core bores in waterproof concrete (white tank)

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® Quick/O
- Wall termination ring
- Expansion resin (selectable)

Sewer pipe	Pipe Ø
Nominal/outer diameter 110	Outer diameter: 110 mm

Dimensions	
Core bore/pipe sleeve Ø	149–153 mm
Minimum wall thickness	200 mm
Outer diameter of seal flange	250 mm

Variant including expansion resin

Product	Article number	VPE
Quadro-Sicura® Quick/O	2620 110 000 10	1 Items
	2620 110 000 16	6 Items

Delivery/price without duct pipe.

Variant excluding expansion resin

Product	Article number	VPE
Quadro-Sicura® Quick/O	2620 110 000 00	1 Items
	2620 110 000 06	6 Items

Delivery/price without duct pipe.



ACCESSORIES – NECESSARY

- 2K cartridge gun