

# Quadro-Sicura® SD

for buildings without basements

NON-PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use as angular penetration in floor slabs made of concrete
- For **cable types** or **water lines**



25 years  
guarantee

## PRODUCT ADVANTAGES

- Suitable for retrofitting for electricity or water through floor slabs
- Quick installation
- Suitable for building renovations

## TECHNICAL DETAILS

- Installation as angular penetration in floor slabs
- Leak-tight against gas and water
- radon proof – according to FHRK information sheet MB101
- For open design
- For the most common pipe and cable diameters
- Integrated plug sealing
- Without additional shrinking
- Suitable for bores in floor slabs made of concrete of load class 2 in accordance with the Waterproofing guideline

## THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® SD
- Expansion resin

Supply lines	Line diameter [mm]
Water or electricity	26–50

Dimensions	
Core bore/pipe sleeve Ø	99–104 mm
Wall thicknesses	200–1200 mm

Further dimensions and versions available upon request.

Product	Dimensions	Article number
Quadro-Sicura® SD PU (packaging unit) 1 item*	26–50 mm (further dimensions possible)	2140 000 001 00
Quadro-Sicura® SD PU (packaging unit) 10 items**	26 – 50 mm (further dimensions possible)	2140 000 010 00

\* including one-item 2K resin system

\*\* including ten-item 2K resin system



HOUSE LEAD-INS



## ACCESSORIES – RECOMMENDED

- 2K cartridge gun