



Quadro-Sicura® building owner's package

Split heat pump

FOR BUILDINGS WITH BASEMENTS

Perfect sealing of refrigerant lines for split heat pumps!



APPLICATION

House-lead-ins for refrigerant lines
Use in the most common wall types with sealing in accordance with DIN 18533 W2.1-E (black tank) and core bores in water-proof concrete (white tank)

PRODUCT ADVANTAGES

- Leak-tight against gas and pressing water
- Casing offers connection option for rigid or flexible jacket pipes/empty ducts with DN 110
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for installation in existing properties
- Gasket insert is to be retrofitted around existing refrigerant lines
- With quick release for safe and secure closure

COMPONENTS/SCOPE OF DELIVERY

1x Quadro-Sicura® Quick/H

Building services duct system with injection system
Casing DN 100 for wall thicknesses from 200–600 mm



25 years
guarantee



1x Curaflex Nova® Uno/M/Z

Gasket insert with replaceable onion ring inserts
DN 100 for refrigerant lines and cables

25 years
guarantee



ACCESSORIES – OPTIONAL

- Fixing tabs
- ITL nut set

ACCESSORIES – NECESSARY

- 2K cartridge gun

Quadro-Sicura® building owner's package, split heat pump for buildings with basements	Outer diameter of cable [mm]	Outer diameter of pipe [inches]	Article number
	2 x 6-15	1/4 + 1/2	2630 110 028 90
	2 x 6-15	3/8 + 5/8	2630 110 027 90
	2 x 6-15	1/4 + 5/8	2630 110 029 90

Prices do not include fixtures and pipes/cables.

inch	Outer diameter
1/4	6,4 mm
1/2	12,7 mm
3/8	9,5 mm
5/8	15,9 mm