

# Quadro-Sicura® Nova 1-FW

for buildings with basements

PRESSING WATER

- Multi-compartment house lead-in **with sealing on both sides**
- Installation in **pre-installed pipe sleeve or core bore in waterproof concrete** (white tank)
- With **additional seal flange** for use in accordance with DIN 18533 W2.1-E (black tank)
- For the following utilities: district/geothermal heating, water, electricity and telecommunications

**25**  
years  
guarantee



## PRODUCT ADVANTAGES

- Infinitely variable modular gaskets for water and energy
- Space-saving building lead-in of supply lines
- Easy assignment of utility seal through symbol identification
- Installation without torque spanner possible

## TECHNICAL DETAILS

- Dry installation
- Leak-tight against gas and pressing water
- radon proof – according to FHRK information sheet MB101
- Split sealing of the respective building services
- Variable arrangement of individual compartments possible
- No additional outer seal required
- Connection option for rigid or flexible jacket pipes DN 75 and DN 125
- Visual indication of the tightening torque via control pins
- With seal flange in accordance with DIN 18533


Supply lines	Pipe/cable Ø
Local/district heating or Geothermal heating	Outer diameter 75 mm, 90 mm, 110 mm; optionally 125 mm  Outer diameter 32 mm, 40 mm, 50 mm Please specify the diameter with your order
Water	Outer diameter: 32 mm, 40 mm, 50 mm; optional outer diameter 63 mm
Electricity	Outer diameter of 25–53 mm
Telecommunications	Outer diameter: 2 × 5–7 mm, 4 × 7–13 mm, 1 × 13 – 21 mm

Dimensions	
Core bore/pipe sleeve Ø	298–304 mm
Wall thicknesses	200–550 mm

Further dimensions and versions available upon request.

Optional diameters	Article number
2 x 75, 90 or 110 mm	2310 075 000 00
2 x 32 – 50 mm	Please specify the diameter with your order

Prices do not include fixtures and pipes/cables.



Variant: Quadro-Sicura® Nova 1-FW/  
breit for twin/element walls