


Quadro-Sicura® E-Quick

for buildings with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** (black tank) or for **core bore in waterproof concrete** (white tank)
- **Utilities: gas, water, electricity or telecommunications**



For water



For tele-
communications



For electricity



For gas



For fibre optic
cables



25
years
guarantee



PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations
- Infinitely variable modular gaskets for water or energy

TECHNICAL DETAILS

- DVGW-approved (RMA, Schuck and VAF-Voigt)
- Leak-tight against gas and pressing water up to 1 bar
- Relining possible when connecting jacket pipes
- Connection option for rigid or flexible jacket pipes DN 75
- The utility is given a dummy plug that is leak-tight against gas and pressing water

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® E3
- Outer seal for Quadro-Sicura® Quick/X
- Expansion resin (selectable)



ACCESSORIES – RECOMMENDED

- 2K cartridge gun



Supply lines	Pipe/cable Ø
Gas or	Gas house lead-ins RMA, Schuck, VAF Voigt, Burger: DN 25 (other dimensions available upon request)
Water or	Outer diameter: 32 mm, 40 mm, 50 mm; optional outer diameter 63 mm
Electricity or	Outer diameter of 25–53 mm
Telecommunications or	Outer diameter: 2 × 5–7 mm, 4 × 7–13 mm, 1 × 13–21 mm
For fibre optic cables (electricity, water, telecommunications, fibre optic cables)	Outer diameter: 1 × 23–40, 1 × 12–16, 2 × 7–13 and 2 × 5–7 mm

Dimensions	
Core bore/pipe sleeve Ø	99–103 mm
Wall thicknesses	240–450 mm
Outer diameter of seal flange	200 mm

Further dimensions and versions available upon request.

Variant including expansion resin

Product	Utility seal	Article number
Quadro-Secura® E-Quick	For RMA gas house lead-in	2 84 1 900 000 1 0
	For Schuck gas house lead-in	2 84 2 900 000 1 0
	For water	2 84 0 900 010 1 0
	For fibre optic cables	2 84 0 900 025 1 0
	For electricity	2 84 0 900 011 1 0
	For telecommunications	2 84 0 900 012 1 0

Prices do not include fixtures and pipes/cables.

Variant excluding expansion resin

Product	Utility seal	Article number
Quadro-Secura® E-Quick	For RMA gas house lead-in	2 84 1 900 000 0 0
	For Schuck gas house lead-in	2 84 2 900 000 0 0
	For water	2 84 0 900 010 0 0
	For fibre optic cables	2 84 0 900 025 0 0
	For electricity	2 84 0 900 011 0 0
	For telecommunications	2 84 0 900 012 0 0

Prices do not include fixtures and pipes/cables.