


Quadro-Sicura® MIS 40

for buildings with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** (black tank) or for **core bore in waterproof concrete** (white tank)
- For **fibre optic cables/pipes** or telecommunication lines



25
Years
Guarantee

PRODUCT ADVANTAGES

- Ideal for sealing existing bitumen thick coatings
- Tensioning and sealing via resin injection using an integrated membrane system
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 1 bar
- radon proof – according to FHRK information sheet MB101
- For open design
- Integrated plug sealing
- Without additional shrinking
- For bores in the most common wall types in accordance with DIN 18533 W2.1-E or for core bore in waterproof concrete (white tank)

▪ THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 40
- Wall termination sleeve
- Grid bow
- Expansion resin
- Quick-clamping device



ACCESSORIES – RECOMMENDED

- 2K cartridge gun

Supply lines	Line diameters
Fibre optic cable/pipes	2 × 5–7 mm or 1 × 9–12 mm

Dimensions	
Core bore/pipe sleeve Ø	40–50 mm
Wall thicknesses	200–900 mm, optionally 900–1200 mm

Product	Line diameter	Article number
Quadro-Sicura® MIS 40 PU (packaging unit) 10 items	for 2 x (5 – 7 mm)	2100 006 000 00
	for 1 x (9 – 12 mm)	2100 012 000 00

Including 10 items from the 2K resin system, one quick-clamping device and 10 grid bows.