


Quadro-Sicura® MIS 90S

for buildings without basements

 PRESSING WATER

- Single-compartment house lead-in with injection system
- Use as angular penetration in floor slabs made of waterproof concrete
- For all cable types or water lines



25
Years
Guarantee

PRODUCT ADVANTAGES

- Allows for the simultaneous routing of electricity or water and telecommunications
- Sealing via resin injection using an integrated membrane system
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Installation as angular penetration in floor slabs
- Leak-tight against gas and pressing water up to 1 bar
- radon proof – according to FHRK information sheet MB101
- For open design
- For the most common pipe and cable diameters
- Integrated plug sealing
- Without additional shrinking
- Suitable for bores in floor slabs made of waterproof concrete, load class 1

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 90S
- Wall termination sleeve
- Expansion resin
- Quick-clamping device
- Selectable collar plugs



ACCESSORIES – RECOMMENDED

- 2K cartridge gun

Supply lines	Line diameter
Water, electricity or telecommunications	1 × 24–40 mm or 3 × 7–12 mm or 1 × 24–52 mm or 1 × 14–21 mm or 3 × 7–13 mm or 1 × 5–13 mm (Please specify the diameter with your order)

Dimensions	
Core bore/pipe sleeve Ø	92–102 mm
Design length	1,300 mm

Further dimensions and versions available upon request.

Product	Line diameter	Article number
Quadro-Sicura® MIS 90S PU (packaging unit) 6 items	1 x 24 – 40 mm and 3 x 7 – 12 mm	2120 040 000 30
	1 x 24 – 52 mm	2120 050 000 30
	1 x 14 – 21 mm, 3 x 7 – 13 mm and 1 x 5 – 13 mm	2120 020 000 30

Including 6 items from the 2K resin system, one quick-clamping device.

