


Quadro-Sicura® Quick/H

for buildings with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** or for **core bore in waterproof concrete (white tank)**
- For holding the **Curaflex Nova® sealing systems**
- With seal flange in accordance with **DIN 18533 (black tank)**
- Ideal for **new connections** in existing buildings



PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 1 bar
- radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- for an open construction
- Integrated casing suitable for the Curaflex Nova® and Curaflex Nova® sealing systems
- Can be sealed to smaller pipe diameters using an adapter sleeve (accessory for type DN 160)
- For bores in the most common wall types with sealing in accordance with DIN 18533 W2.1-E and for core bores in waterproof concrete (white tank)
- Casing offers connection option for rigid or flexible jacket pipes
- Relining possible when connecting jacket pipes

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® Quick/H
- Wall termination ring
- Expansion resin (selectable)



ACCESSORIES – NECESSARY

- Curaflex Nova® sealing systems
- adapter sleeve 160/125 bzw. 160/140
- 2K-cartridge gun

Typ DN/OD [mm]	Inner diameter of casing-Ø [mm]	Core bore/pipe sleeve-Ø [mm]	Outer diameter of seal flange [mm]
110	100	149 – 153	250
160	150	199 – 203	300

Dimensions	
wall thickness	200 – 600 mm, optional to 1200 mm

Variant including expansion resin

Product	Typ	Article number
Quadro-Sicura® Quick/H	110	2630 110 760 10
Quadro-Sicura® Quick/H	160	2630 160 760 10

Preis ohne Curaflex® Dichtungssystem und Leitung.

Variant excluding expansion resin

Product	Typ	Article number
Quadro-Sicura® Quick/H	110	2630 110 760 00
Quadro-Sicura® Quick/H	160	2630 160 760 00

Price without Curaflex® sealing system and pipe

adapter sleeve 160/125 resp. 160/140

adapter sleeve [DN]	Sealing on	Article number
160/125	110 - 125 mm	2990 160 125 00
160/140	130 - 145 mm	2990 160 140 00



Installation example

