


Quadro-Sicura® Quick/O

for buildings with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** or for **core bore in waterproof concrete (white tank)**
- For sealing **sewer pipes DN DN/OD 110 or DN/OD 160**
- With seal flange in accordance with **DIN 18533 (black tank)**
- Ideal for **new connections** in existing buildings



PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 1 bar
- radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- For open design
- For bores in the most common wall types with sealing in accordance with DIN 18533 W2.1-E and for core bores in waterproof concrete (white tank)

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® Quick/O
- Wall termination ring
- Expansion resin (selectable)

Sewer pipe DN/OD [mm]	Core bore/pipe sleeve-Ø [mm]	Outer diameter of seal flange [mm]
110	149 – 153	250
160	199 – 203	300

Dimensions	
Minimum wall thickness	200 mm

Variant including expansion resin

Product	DN/OD	Article number	VPE
Quadro-Sicura® Quick/O	110	2620 110 000 10	1 Items
Quadro-Sicura® Quick/O	110	2620 110 000 16	6 Items
Quadro-Sicura® Quick/O	160	2620 160 000 10	1 Items

Delivery/price without duct pipe.

Variant excluding expansion resin

Product	DN/OD	Article number	VPE
Quadro-Sicura® Quick/O	110	2620 110 000 00	1 Items
Quadro-Sicura® Quick/O	110	2620 110 000 06	6 Items
Quadro-Sicura® Quick/O	160	2620 160 000 00	1 Items

Delivery/price without duct pipe.



ACCESSORIES – NECESSARY

- 2K cartridge gun