


Quadro-Sicura® E2

for buildings with basements

 PRESSING WATER

- Single-compartment house lead-in **with sealing on both sides**
- Installation in **pre-installed pipe sleeve or core bore in waterproof concrete (white tank)**
- For the following utilities: gas, water, electricity and telecommunications



25 years
guarantee



PRODUCT ADVANTAGES

- Infinitely variable modular gaskets for water or energy

TECHNICAL DETAILS

- DVGW-approved
- Leak-tight against gas and pressing water
- radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- Optionally, methane gas resistant design is available
- Optional installation in accordance with DIN 18533 possible
- Dry installation
- Relining possible when connecting jacket pipes
- Connection option for rigid or flexible jacket pipes DN 75
- The utility is given a dummy plug that is leak-tight against gas and pressing water

| Supply lines | Pipe/cable Ø |
|---|--|
| Gas or | Gas house lead-ins RMA, Schuck, VAF Voigt, Burger: DN 25 (other dimensions available upon request) |
| Water or | Outer diameter: 32 mm, 40 mm, 50 mm; optional outer diameter 63 mm |
| Electricity or | Outer diameter of 25–53 mm |
| Telecommunications or | Outer diameter: 2 × 5–7 mm, 4 × 7–13 mm, 1 × 13–21 mm |
| For fibre optic cables (electricity, water, telecommunications, fibre optic cables) | Outer diameter: 2 × 5–7 mm, 2 × 7–13 mm, 1 × 12–16 mm, 1 × 23–40 mm |
| Dimensions | |
| Core bore/pipe sleeve Ø | 99–103 mm |
| Wall thicknesses | 130–550 mm |

Further dimensions available upon request.

| Utility seal | Article number |
|--|-----------------|
| For RMA gas house lead-in | 2821 000 000 00 |
| For Schuck gas house lead-in | 2822 000 000 00 |
| For water | 2820 000 010 00 |
| For electricity, water, telecommunications, fibre optic cables | 2820 000 025 00 |
| For energy | 2820 000 011 00 |
| For telecom | 2820 000 012 00 |

Prices do not include fixtures and pipes/cables.