


# UGA BKD 150 system cap

With sockets and heat shrink sleeves

 PRESSING WATER

- Use in existing flange sleeves and mounting flange
- Sealing of media lines using shrink technology
- With bayonet closure



## PRODUCT ADVANTAGES

- Gas and water-tight
- For laying media lines (cables or pipes) measuring 7–108 mm
- Sealing with heat or cold-shrink technology
- Compatible with other established systems
- Made of environmentally friendly and chemically highly resistant materials

## System cap closed

Article	Cables	Article number
BKD150-D	0	4 10 1 000 150 0 4

## System cap with heat shrink sleeve

Article	Cables	Outer diameter of pipe/cable	Article number
BKD150-D-1/80-TM	1	26–78 mm	4 10 1 080 150 04
BKD150-D-1/110-TM	1	34–108 mm	4 10 1 110 150 04
BKD150-D-3/59(3/3)-TM	3	22–57 mm	4 10 1 059 150 04
BKD150-D-7/38(7/6)-TM*	7	7–37 mm	4 10 1 038 150 04
BKD150-D-8/35(4/2)/25(4/2)-TM**	8	4× 7–24 mm / 4× 7–34 mm	4 10 1 035 150 04

## System cap with cold shrink sleeve

Article	Cables	Outer diameter of pipe/cable
BKD150-D-1/80-KS	1	33–79 mm
BKD150-D-1/110-KS	1	38–109 mm
BKD150-D-3/59(3/3)-KS	3	21–57 mm
BKD150-D-7/38(7/6)-KS*	7	20–37 mm
BKD150-D-8/35(4/2)/25(4/2)-KS**	8	4× 11–24 mm / 4× 16–34 mm

\* BKD150-D-7 includes one closed socket in the scope of delivery, which can be opened up as needed. The scope of delivery includes six shrink sleeves.

\*\* BKD150-D-8 includes four closed sockets in the scope of delivery (two each of 35 and 25 mm), which can be opened up as needed. The scope of delivery includes four shrink sleeves; further shrink sleeves are available as accessories in sets of four.

The UGA range is excluded from the DOYMA 25-year warranty.