

UGA GPD with interchangeable insert




Rubber press seal



PRESSING WATER

- Use in on-site casing or waterproof concrete core bore (white tank)
- Hinged design, for pipes that are already installed
- With replaceable interchangeable insert



PRODUCT ADVANTAGES

- Custom-made for your application
- For retrofitting around existing pipes
- Quick installation
- Interchangeable insert with collar for a secure hold in the rubber press seal
- The split interchangeable insert inside can be replaced with a new one without the entire component having to be removed

TECHNICAL DETAILS

- Certified under FHRK test regulation GE 101 (no. G 30 322-7-2)
- All metal parts made of stainless steel 1.4301 (V2A), optionally also stainless steel 1.4571/1.4404 (V4A)
- Split version
- Leak-tight against gas and pressing water
- Can accommodate slight axial movements

PRODUCT SCOPE

- Rubber press seal (gasket insert) made of EPDM
- Interchangeable insert with collar (except WE 125) made of EPDM

The UGA range is excluded from the DOYMA 25-year warranty.



GPD with interchangeable insert

Article	Examples for max. utilisation*
GPD100/G/60/WE65/V2A/EPDM (Z)x(D)	3 × Ø 22 or 5 × Ø 17 or 9 × Ø 12
GPD125/G/60/WE85/V2A/EPDM (Z)x(D)	3 × Ø 30 or 5 × Ø 24 or 9 × Ø 16
GPD150/G/60/WE110/V2A/EPDM (Z)x(D)	3 × Ø 42 or 5 × Ø 34 or 9 × Ø 24
GPD200/G/60/WE125/V2A/EPDM (Z)x(D)	3 × Ø 50 or 5 × Ø 38 or 9 × Ø 27

* Other combinations with different diameters are also possible.

Individual interchangeable insert (optional)

Article
WE65/G/60/EPDM (Z)x(D)
WE85/G/60/EPDM (Z)x(D)
WE110/G/60/EPDM (Z)x(D)
WE125/G/60/EPDM (Z)x(D)