

# UGA KD 110 system cover



## Conical system insert



PRESSING WATER

- Use in existing sealing collars on the connection side
- With screw closure



## PRODUCT ADVANTAGES

- Conical system insert for sealing cables and cable protection pipes
- Easy installation
- Custom-made for your application
- Split version for installing after cables have been laid

The UGA range is excluded from the DOYMA 25-year warranty.



Article		Article number
KD110-D-DGM110	110 mm outer diameter of pipe/cable	4 11 2 110 110 0 4
KD110-E-WE/O/EPDM	blind cap	4 11 2 000 111 0 4
KD110-E-WE/EPDM (Z) × (D)	1 to 5 bores	—
	6+ bores	—

#### Assignment table for WA conical system insert

Article	Number of bores	D max. outer diameter*
KD110-E-WE/EPDM 1 × (D)	1	Up to 110 mm
KD110-E-WE/EPDM 3 × (D)	3	Up to 48 mm
KD110-E-WE/EPDM 5 × (D)	5	Up to 36 mm
KD110-E-WE/EPDM 7 × (D)	7	Up to 32 mm
KD110-E-WE/EPDM 9 × (D)	9	Up to 26 mm
KD110-E-WE/EPDM 13 × (D)	13	Up to 21 mm
KD110-E-WE/EPDM 19 × (D)	19	Up to 18 mm
KD110-E-WE/EPDM 28 × (D)	28	Up to 14 mm

\* Other combinations with different diameters are also possible.