

Curaflex® ring closure RRV

Protection against dirt and splash water

- For sealing of annulus spaces
- Use in on-site pipe sleeve or waterproof concrete core bore (white tank)
- High variability



PRODUCT ADVANTAGES

- High variability through an elastic adaptation to the existing pipe
- Easy installation
- Ideal for combining with any Curaflex® gasket insert
- Adaptability to the media pipe

TECHNICAL DETAILS

- Permanent tight closure for core bores and pipe sleeves
- Dust and splash water protection (IP54)
- Can accommodate axial movements
- Manually adaptable to the media pipe
- DN 100 plugged sealing and from 20–63 mm
- DN 200 plugged sealing and from 108–160 mm

MATERIAL

- DOYMA-Grip (EPDM)

Inner diameter of pipe sleeve/core bore D_1 [DN in mm]	Outer diameter of pipe/cable d [mm]	Article number
100 (99–104)	1 × 20–31 2 × 5 2 × 7	1 18 5 000 100 0 0
	1 × 32–45 2 × 5 2 × 7	
	1 × 46–63 2 × 5 2 × 7	
200 (199–203)	1 × 108–135 2 × 5 2 × 7	1 18 5 000 200 0 0
	1 × 136–160 2 × 5 2 × 7	

L_0 (max. design length) [mm]: ≤ 85 mm

