

HKD DOMO-V/ HKD DOMO-VT

PRESSING WATER

- Use in **on-site casing** or **waterproof concrete core bore** (white tank)



The HKD DOMO-V models can be variably adjusted to the diameter of the pipe or cable. One HKD DOMO-V type can therefore replace up to 10 standard sizes. The HKD DOMO-VT type is hinged for use on pipes that have already been installed. It is adapted to the relevant diameter by simply removing the rubber elements that are not required.

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-6)
- Leak-tight against pressing water
- HKD DOMO-VT: hinged design, for pipes that are already installed with casing/core bore DN 100
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material: EPDM 40 mm wide
- Gas-tight

ACCESSORIES

- Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.

HKD DOMO-V/HKD DOMO-VT

Type	Inner diameter of casing/core bore [DN in mm]	Outer diameter of pipe/cable [mm]	V2A Article number
DOMO-V 100	DN 100 (99-102)	0 (plugged)	8 88 0 000 100 2 0
		18-19	
		20-24	
		25-29	
		30-34	
		35-39	
		40-44	
		45-49	
		50-54	
		55-59	
		60-65	
		DOMO-VT 100	
32			
40			
50			
63			
DOMO-V 150	DN 150 (149-152)	0 (plugged)	8 88 0 000 150 2 0
		62-63	
		75-77	
		88-90	
		108-110	
DOMO-V 200	DN 200 (199-202)	0 (plugged)	8 88 0 000 200 2 0
		108-110	
		123-125	
		133-135	
		158-160	

V4A upon request.

E-MT-1-904

Subject to technical changes. Some illustrations include accessories.