

# HKD DOMO-DW-NK

**PRESSING WATER**

- Use in **on-site casing** or **waterproof concrete core bore** (white tank)



The HKD DOMO-DW-NK features robust craftsmanship quality. **For gentle sealing of plastic jacket pipes. Can also be used for twin/element walls.**

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-6)
- Leak-tight against pressing water (80 mm seal width)
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material is solid EPDM rubber, extra soft
- Gas-tight

## **ACCESSORIES**

- Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.

## HKD DOMO-DW-NK

Inner diameter of casing/core bore [DN in mm]	Outer diameter of pipe/cable d [mm]	V2A	V4A
		Article number	Article number
80 (79–83)	11 – 13	8 03 4 012 080 2 0	8 03 4 012 080 4 0
	14 – 16	8 03 4 015 080 2 0	8 03 4 015 080 4 0
	17 – 19	8 03 4 017 080 2 0	8 03 4 017 080 4 0
	20 – 22	8 03 4 022 080 2 0	8 03 4 022 080 4 0
	25 – 27	8 03 4 025 080 2 0	8 03 4 025 080 4 0
	28 – 31	8 03 4 028 080 2 0	8 03 4 028 080 4 0
	32 – 35	8 03 4 032 080 2 0	8 03 4 032 080 4 0
	36 – 40	8 03 4 040 080 2 0	8 03 4 040 080 4 0
100 (99–103)	12 – 16	8 03 4 015 100 2 0	8 03 4 015 100 4 0
	17 – 21	8 03 4 020 100 2 0	8 03 4 020 100 4 0
	22 – 26	8 03 4 025 100 2 0	8 03 4 025 100 4 0
	27 – 31	8 03 4 028 100 2 0	8 03 4 028 100 4 0
	32 – 35	8 03 4 032 100 2 0	8 03 4 032 100 4 0
	36 – 40	8 03 4 040 100 2 0	8 03 4 040 100 4 0
	41 – 44	8 03 4 042 100 2 0	8 03 4 042 100 4 0
	48 – 51	8 03 4 050 100 2 0	8 03 4 050 100 4 0
	52 – 54	8 03 4 054 100 2 0	8 03 4 054 100 4 0
	55 – 56	8 03 4 056 100 2 0	8 03 4 056 100 4 0
	57 – 57	8 03 4 057 100 2 0	8 03 4 057 100 4 0
	58 – 58	8 03 4 058 100 2 0	8 03 4 058 100 4 0
125 (124–128)	57 – 61	8 03 4 060 125 2 0	8 03 4 060 125 4 0
	62 – 64	8 03 4 063 125 2 0	8 03 4 063 125 4 0
	73 – 75	8 03 4 075 125 2 0	8 03 4 075 125 4 0
	76 – 77	8 03 4 076 125 2 0	8 03 4 076 125 4 0
150 (149–153)	57 – 60	8 03 4 060 150 2 0	8 03 4 060 150 4 0
	74 – 77	8 03 4 075 150 2 0	8 03 4 075 150 4 0
	78 – 80	8 03 4 078 150 2 0	8 03 4 078 150 4 0
	88 – 91	8 03 4 090 150 2 0	8 03 4 090 150 4 0
	98 – 100	8 03 4 098 150 2 0	8 03 4 098 150 4 0
	101 – 104	8 03 4 102 150 2 0	8 03 4 102 150 4 0
	108 – 110	8 03 4 110 150 2 0	8 03 4 110 150 4 0
	111 – 115	8 03 4 114 150 2 0	8 03 4 114 150 4 0

Inner diameter of casing/core bore [DN in mm]	Outer diameter of pipe/cable d [mm]	V2A	V4A	
		Article number	Article number	
200 (199–204)	78 – 81	8 03 4 078 200 2 0	8 03 4 078 200 4 0	
	86 – 90	8 03 4 090 200 2 0	8 03 4 090 200 4 0	
	108 – 112	8 03 4 110 200 2 0	8 03 4 110 200 4 0	
	113 – 115	8 03 4 114 200 2 0	8 03 4 114 200 4 0	
	116 – 118	8 03 4 118 200 2 0	8 03 4 118 200 4 0	
	123 – 126	8 03 4 125 200 2 0	8 03 4 125 200 4 0	
	133 – 136	8 03 4 135 200 2 0	8 03 4 135 200 4 0	
	137 – 141	8 03 4 140 200 2 0	8 03 4 140 200 4 0	
	142 – 145	8 03 4 144 200 2 0	8 03 4 144 200 4 0	
	159 – 160	8 03 4 160 200 2 0	8 03 4 160 200 4 0	
	250 (247–253)	105 – 109	8 03 4 108 250 2 0	8 03 4 108 250 4 0
		110 – 113	8 03 4 110 250 2 0	8 03 4 110 250 4 0
114 – 118		8 03 4 114 250 2 0	8 03 4 114 250 4 0	
123 – 126		8 03 4 125 250 2 0	8 03 4 125 250 4 0	
132 – 136		8 03 4 135 250 2 0	8 03 4 135 250 4 0	
137 – 141		8 03 4 140 250 2 0	8 03 4 140 250 4 0	
142 – 144		8 03 4 144 250 2 0	8 03 4 144 250 4 0	
148 – 152		8 03 4 148 250 2 0	8 03 4 148 250 4 0	
158 – 162		8 03 4 160 250 2 0	8 03 4 160 250 4 0	
168 – 170		8 03 4 170 250 2 0	8 03 4 170 250 4 0	
174 – 177		8 03 4 175 250 2 0	8 03 4 175 250 4 0	
178 – 181		8 03 4 180 250 2 0	8 03 4 180 250 4 0	
300 (297–304)	158 – 162	8 03 4 160 300 2 0	8 03 4 160 300 4 0	
	168 – 170	8 03 4 170 300 2 0	8 03 4 170 300 4 0	
	200 – 204	8 03 4 200 300 2 0	8 03 4 200 300 4 0	
	209 – 212	8 03 4 210 300 2 0	8 03 4 210 300 4 0	
	219 – 223	8 03 4 222 300 2 0	8 03 4 222 300 4 0	
	224 – 226	8 03 4 225 300 2 0	8 03 4 225 300 4 0	
350 (347–353)	240 – 244	8 03 4 242 350 2 0	8 03 4 242 350 4 0	
	249 – 253	8 03 4 250 350 2 0	8 03 4 250 350 4 0	
	271 – 275	8 03 4 271 350 2 0	8 03 4 271 350 4 0	
	278 – 280	8 03 4 280 350 2 0	8 03 4 280 350 4 0	
400 (397–403)	312 – 316	8 03 4 315 400 2 0	8 03 4 315 400 4 0	
	322 – 325	8 03 4 324 400 2 0	8 03 4 324 400 4 0	
	326 – 329	8 03 4 326 400 2 0	8 03 4 326 400 4 0	
450 (447–453)	353 – 356	8 03 4 355 450 2 0	8 03 4 355 450 4 0	
500 (497–503)	398 – 401	8 03 4 400 500 2 0	8 03 4 400 500 4 0	
	406 – 410	8 03 4 406 500 2 0	8 03 4 406 500 4 0	
	426 – 430	8 03 4 429 500 2 0	8 03 4 429 500 4 0	
600 (597–603)	448 – 451	8 03 4 450 600 2 0	8 03 4 450 600 4 0	
	508 – 510	8 03 4 508 600 2 0	8 03 4 508 600 4 0	