

HKD DOMO-DW-T

PRESSING WATER

- Use in **on-site casing** or **waterproof concrete core bore** (white tank)



The HKD DOMO-DW-T features robust craftsmanship quality. **The split version for retrofitting is hinged and can be used on pipes that have already been installed.**

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-6)
- Leak-tight against pressing water (40 mm seal width)
- Hinged version, for pipes that are already installed
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material is solid EPDM rubber, optionally NBR
- Gas-tight



ACCESSORIES

- Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.

HKD DOMO-DW-T

Inner diameter of casing/core bore [DN in mm]	Outer diameter of pipe/cable d [mm]	V2A	V4A
		Article number	Article number
80 (79–83)	11 – 13	8 03 2 012 080 2 0	8 03 2 012 080 4 0
	14 – 16	8 03 2 015 080 2 0	8 03 2 015 080 4 0
	17 – 19	8 03 2 017 080 2 0	8 03 2 017 080 4 0
	20 – 22	8 03 2 022 080 2 0	8 03 2 022 080 4 0
	25 – 27	8 03 2 025 080 2 0	8 03 2 025 080 4 0
	28 – 31	8 03 2 028 080 2 0	8 03 2 028 080 4 0
	32 – 35	8 03 2 032 080 2 0	8 03 2 032 080 4 0
	36 – 40	8 03 2 040 080 2 0	8 03 2 040 080 4 0
100 (99–103)	12 – 16	8 03 2 015 100 2 0	8 03 2 015 100 4 0
	17 – 21	8 03 2 020 100 2 0	8 03 2 020 100 4 0
	22 – 26	8 03 2 025 100 2 0	8 03 2 025 100 4 0
	27 – 31	8 03 2 028 100 2 0	8 03 2 028 100 4 0
	32 – 35	8 03 2 032 100 2 0	8 03 2 032 100 4 0
	36 – 40	8 03 2 040 100 2 0	8 03 2 040 100 4 0
	41 – 44	8 03 2 042 100 2 0	8 03 2 042 100 4 0
	48 – 51	8 03 2 050 100 2 0	8 03 2 050 100 4 0
	52 – 54	8 03 2 054 100 2 0	8 03 2 054 100 4 0
	55 – 56	8 03 2 056 100 2 0	8 03 2 056 100 4 0
	57 – 57	8 03 2 057 100 2 0	8 03 2 057 100 4 0
	58 – 58	8 03 2 058 100 2 0	8 03 2 058 100 4 0
125 (124–128)	57 – 61	8 03 2 060 125 2 0	8 03 2 060 125 4 0
	62 – 64	8 03 2 063 125 2 0	8 03 2 063 125 4 0
	73 – 75	8 03 2 075 125 2 0	8 03 2 075 125 4 0
	76 – 77	8 03 2 076 125 2 0	8 03 2 076 125 4 0
150 (149–153)	57 – 60	8 03 2 060 150 2 0	8 03 2 060 150 4 0
	74 – 77	8 03 2 075 150 2 0	8 03 2 075 150 4 0
	78 – 80	8 03 2 078 150 2 0	8 03 2 078 150 4 0
	88 – 91	8 03 2 090 150 2 0	8 03 2 090 150 4 0
	98 – 100	8 03 2 098 150 2 0	8 03 2 098 150 4 0
	101 – 104	8 03 2 102 150 2 0	8 03 2 102 150 4 0
	108 – 110	8 03 2 110 150 2 0	8 03 2 110 150 4 0
	111 – 115	8 03 2 114 150 2 0	8 03 2 114 150 4 0

Inner diameter of casing/core bore [DN in mm]	Outer diameter of pipe/cable d [mm]	V2A	V4A
		Article number	Article number
200 (199–204)	78 – 81	8 03 2 078 200 2 0	8 03 2 078 200 4 0
	86 – 90	8 03 2 090 200 2 0	8 03 2 090 200 4 0
	108 – 112	8 03 2 110 200 2 0	8 03 2 110 200 4 0
	113 – 115	8 03 2 114 200 2 0	8 03 2 114 200 4 0
	116 – 118	8 03 2 118 200 2 0	8 03 2 118 200 4 0
	123 – 126	8 03 2 125 200 2 0	8 03 2 125 200 4 0
	133 – 136	8 03 2 135 200 2 0	8 03 2 135 200 4 0
	137 – 141	8 03 2 140 200 2 0	8 03 2 140 200 4 0
	142 – 145	8 03 2 144 200 2 0	8 03 2 144 200 4 0
	159 – 160	8 03 2 160 200 2 0	8 03 2 160 200 4 0
	105 – 109	8 03 2 108 250 2 0	8 03 2 108 250 4 0
	110 – 113	8 03 2 110 250 2 0	8 03 2 110 250 4 0
250 (247–253)	114 – 118	8 03 2 114 250 2 0	8 03 2 114 250 4 0
	123 – 126	8 03 2 125 250 2 0	8 03 2 125 250 4 0
	132 – 136	8 03 2 135 250 2 0	8 03 2 135 250 4 0
	137 – 141	8 03 2 140 250 2 0	8 03 2 140 250 4 0
	142 – 144	8 03 2 144 250 2 0	8 03 2 144 250 4 0
	148 – 152	8 03 2 148 250 2 0	8 03 2 148 250 4 0
	158 – 162	8 03 2 160 250 2 0	8 03 2 160 250 4 0
	168 – 170	8 03 2 170 250 2 0	8 03 2 170 250 4 0
	174 – 177	8 03 2 175 250 2 0	8 03 2 175 250 4 0
	178 – 181	8 03 2 180 250 2 0	8 03 2 180 250 4 0
	158 – 162	8 03 2 160 300 2 0	8 03 2 160 300 4 0
	168 – 170	8 03 2 170 300 2 0	8 03 2 170 300 4 0
300 (297–304)	200 – 204	8 03 2 200 300 2 0	8 03 2 200 300 4 0
	209 – 212	8 03 2 210 300 2 0	8 03 2 210 300 4 0
	219 – 223	8 03 2 222 300 2 0	8 03 2 222 300 4 0
	224 – 226	8 03 2 225 300 2 0	8 03 2 225 300 4 0
350 (347–353)	240 – 244	8 03 2 242 350 2 0	8 03 2 242 350 4 0
	249 – 253	8 03 2 250 350 2 0	8 03 2 250 350 4 0
	271 – 275	8 03 2 271 350 2 0	8 03 2 271 350 4 0
	278 – 280	8 03 2 280 350 2 0	8 03 2 280 350 4 0
400 (397–403)	312 – 316	8 03 2 315 400 2 0	8 03 2 315 400 4 0
	322 – 325	8 03 2 324 400 2 0	8 03 2 324 400 4 0
	326 – 329	8 03 2 326 400 2 0	8 03 2 326 400 4 0
450 (447–453)	353 – 356	8 03 2 355 450 2 0	8 03 2 355 450 4 0
500 (497–503)	398 – 401	8 03 2 400 500 2 0	8 03 2 400 500 4 0
	406 – 410	8 03 2 406 500 2 0	8 03 2 406 500 4 0
	426 – 430	8 03 2 429 500 2 0	8 03 2 429 500 4 0
600 (597–603)	448 – 451	8 03 2 450 600 2 0	8 03 2 450 600 4 0
	508 – 510	8 03 2 508 600 2 0	8 03 2 508 600 4 0

For further standard dimensions per DN, see page 2. All of the special seals deviating from the standard are delivered as type HKD DISO with 40 mm EPDM elastomer, with 2 × 40 mm EPDM elastomer for DN 800 and higher, for pressing and non-pressing water, and in stainless steel 1.4301 (V2A/Inox 304). The HKD DISO is optionally also available in stainless steel 1.4571 (V4A/Inox 316) and with other elastomer compounds, such as NBR.