



HKD KG 2000 sewer bend

 PRESSING WATER

- Use in unfinished floor slabs to be made of waterproof concrete (white tank)



- KG 2000 sewer bend with seal element made of EPDM
- Seal element leak-tight against gas and pressing water
- Polypropylene solid-walled pipe; more impact-resistant and more abrasion-resistant than KG
- KG 2000 sewer pipes in accordance with DIN EN 14758
- Leak-tight upon installation in a white tank floor, if no floor element can be installed due to space constraints.
- Bend with 15°/30°/45°/68°

KG 2000 sewer bend 15°

Nominal size [DN in mm]	Article number
100	8 20 1 100 015 1 0
125	8 20 1 125 015 1 0
150	8 20 1 150 015 1 0
200	8 20 1 200 015 1 0

KG 2000 sewer bend 30°

Nominal size [DN in mm]	Article number
100	8 20 1 100 030 1 0
125	8 20 1 125 030 1 0
150	8 20 1 150 030 1 0
200	8 20 1 200 030 1 0

KG 2000 sewer bend 45°

Nominal size [DN in mm]	Article number
100	8 20 1 100 045 1 0
125	8 20 1 125 045 1 0
150	8 20 1 150 045 1 0
200	8 20 1 200 045 1 0

KG 2000 sewer bend 68°

Nominal size [DN in mm]	Article number
100	8 20 1 100 068 1 0
125	8 20 1 125 068 1 0
150	8 20 1 150 068 1 0
200	8 20 1 200 068 1 0

The HKD range is excluded from the DOYMA 25-year warranty.