



HKD KG 2000

sewer wall element

 PRESSING WATER

- Use in **unfinished walls to be made of waterproof concrete** (white tank)



- KG 2000 sewer pipe as double sleeve with seal element made of EPDM
- Leak-tight against gas and pressing water upon installation in a white tank wall
- KG 2000 sewer pipes in accordance with DIN EN 14758
- Polypropylene solid-walled pipe; more impact-resistant and more abrasion-resistant than KG
- For wall thicknesses of 200–500 mm
- Including installation aids/cover

Nominal size [DN in mm]	Length [mm]	Article number
100	200	8 20 0 100 200 1 0
	240	8 20 0 100 240 1 0
	250	8 20 0 100 250 1 0
	300	8 20 0 100 300 1 0
	350	8 20 0 100 350 1 0
	365	8 20 0 100 365 1 0
	400	8 200 100 400 1 0
125	200	8 20 0 125 200 1 0
	240	8 20 0 125 240 1 0
	250	8 20 0 125 250 1 0
	300	8 20 0 125 300 1 0
	350	8 20 0 125 350 1 0
	365	8 20 0 125 365 1 0
	400	8 20 0 125 400 1 0
150	200	8 20 0 150 200 1 0
	240	8 20 0 150 240 1 0
	250	8 20 0 150 250 1 0
	300	8 20 0 150 300 1 0
	350	8 20 0 150 350 1 0
	365	8 20 0 150 365 1 0
	400	8 20 0 150 400 1 0
200	240	8 20 0 200 240 1 0
	250	8 20 0 200 250 1 0
	300	8 20 0 200 300 1 0
	350	8 20 0 200 350 1 0
	365	8 20 0 200 365 1 0
	400	8 20 0 200 400 1 0
	500	8 20 0 200 500 1 0

The HKD range is excluded from the DOYMA 25-year warranty.

