# **HKD KG**

# sewer floor element




PRESSING WATER

Use in unfinished floor slabs to be made of waterproof concrete (white tank)











- KG sewer pipe as sleeve with seal element made of EPDM
- Leak-tight against gas and pressing water upon installation in the floor slab
- KG sewer pipes in accordance with DIN EN 13476-2
- Length approx. 500 mm
- Optionally also available with foil flange for connecting moisture barriers in the form of tanking membranes

#### Without foil flange

Nominal size [DN in mm]	Article number
100	8 20 1 100 500 0 0
125	8 20 1 125 500 0 0
150	8 20 1 150 500 0 0
200	8 20 1 200 500 0 0

#### With foil flange

•	
Nominal size [DN in mm]	Article number
100	8 20 1 100 500 0 1
125	8 20 1 125 500 0 1
150	8 20 1 150 500 0 1
200	8 20 1 200 500 0 1

## **OPTIONAL ACCESSORIES**

APP-PU 50	Article number
Accessories for foil flanges	8 99 0 050 000 0 0

Further information can be found on the HKD APP-PU 50 product page.



### **ACCESSORIES**

One-component polyurethane sealant material APP-PU 50 with a very good adhesion to steel, plastics and concrete.

The HKD range is excluded from the DOYMA 25-year warranty.

