


# HKD KG

## sewer wall element

 PRESSING WATER

- Use in **unfinished walls to be made of waterproof concrete** (white tank)



- KG sewer pipe as double sleeve with seal element made of EPDM
- Leak-tight against gas and pressing water upon installation in a white tank wall
- KG sewer pipes in accordance with EN 13476-2
- Wall thicknesses 200–500 mm
- Including installation aids/cover

The HKD range is excluded from the DOYMA 25-year warranty.



## HKD KG-sewer wall element

Nominal size [DN in mm]	Length [mm]	Article number
100	200	8 20 0 100 200 0 0
	240	8 20 0 100 240 0 0
	250	8 20 0 100 250 0 0
	300	8 20 0 100 300 0 0
	350	8 20 0 100 350 0 0
	365	8 20 0 100 365 0 0
	400	8 20 0 100 400 0 0
	500	8 20 0 100 500 0 0
125	200	8 20 0 125 200 0 0
	240	8 20 0 125 240 0 0
	250	8 20 0 125 250 0 0
	300	8 20 0 125 300 0 0
	350	8 20 0 125 350 0 0
	365	8 20 0 125 365 0 0
	400	8 20 0 125 400 0 0
	500	8 20 0 125 500 0 0
150	200	8 20 0 150 200 0 0
	240	8 20 0 150 240 0 0
	250	8 20 0 150 250 0 0
	300	8 20 0 150 300 0 0
	350	8 20 0 150 350 0 0
	365	8 20 0 150 365 0 0
	400	8 20 0 150 400 0 0
	500	8 20 0 150 500 0 0
200	240	8 20 0 200 240 0 0
	250	8 20 0 200 250 0 0
	300	8 20 0 200 300 0 0
	350	8 20 0 200 350 0 0
	365	8 20 0 200 365 0 0
	400	8 20 0 200 400 0 0
	500	8 20 0 200 500 0 0