


HKD DOMO-NW-M

 NON-PRESSING WATER

- Use in **on-site casing** or **waterproof concrete core bore** (white tank)



The HKD DOMO-NW-M features robust craftsmanship quality.
For sealing multiple pipes and cables in one opening.

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-7)
- Leak-tight against non-pressing water (20 mm seal width)
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material is solid EPDM rubber, optionally NBR
- Gas-tight



ACCESSORIES

- Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.

HKD DOMO-NW-M

Inner diameter of casing/core bore [DN in mm]	Outer diameter of pipe/cable [mm]	Number of pipes or cables
80 (79–83)	5–25/5–15	1–2/1–2
	5–15	1–7
100 (99–103)	10–35/5–20	1–2/1–2
	5–25	1–4
	10–50/5–20	1/1
	10–40/5–20	1/1–2
	5–20	1–7
125 (124–128)	10–40/5–30	1–2/1–2
	10–35	1–4
	5–25	1–7
150 (149–153)	10–50/10–35	1–2/1–2
	10–30	1–7
	10–50	1–3
200 (199–204)	10–50/5–20	1–3/1–4
	10–50	1–5
	40–65	1–4

No article numbers. Precise outer diameter and number of pipes must be specified in your order.

All of the special seals deviating from the standard are delivered as type HKD DISO with 40 mm EPDM elastomer, with 2 × 40 mm EPDM elastomer for DN 800 and higher, for pressing and non-pressing water, and in stainless steel 1.4301 (V2A/Inox 304). The HKD DISO is optionally also available in a split version for pipes that are already installed, in stainless steel 1.4571 (V4A/Inox 316) and with other elastomer compounds, such as NBR.