

HKD KE casing

NON-PRESSING WATER

PRESSING WATER

- Use in unfinished structures or parts of structures to be made of waterproof concrete (white tank)



- The inner diameter matches the nominal diameter DN exactly
- High dimensional stability
- Lightweight, impact-resistant plastic
- With seal element made of EPDM
- Leak-tight against non-pressing and pressing water
- Gas-tight
- Seal element certified to be leak-tight against pressing water at 4 bar
- Lengths: 200–500 mm

NOTE

- New variant arriving in 2nd quarter of 2020. This variant will also have a bonding flange for sealing in accordance with DIN 18533 (black tank).

ACCESSORIES

- Formwork fastener (1701), see Curaflex® accessories

Nominal size [DN in mm]	Length [mm]	Article number
100	200	8 10 0 100 200 0 0
	250	8 10 0 100 250 0 0
	300	8 10 0 100 300 0 0
	350	8 10 0 100 350 0 0
	400	8 10 0 100 400 0 0
	500	8 10 0 100 500 0 0
125	200	8 10 0 125 200 0 0
	250	8 10 0 125 250 0 0
	300	8 10 0 125 300 0 0
	350	8 10 0 125 350 0 0
	400	8 10 0 125 400 0 0
	500	8 10 0 125 500 0 0
150	200	8 10 0 150 200 0 0
	250	8 10 0 150 250 0 0
	300	8 10 0 150 300 0 0
	350	8 10 0 150 350 0 0
	400	8 10 0 150 400 0 0
	500	8 10 0 150 500 0 0
200	200	8 10 0 200 200 0 0
	250	8 10 0 200 250 0 0
	300	8 10 0 200 300 0 0
	350	8 10 0 200 350 0 0
	400	8 10 0 200 400 0 0
	500	8 10 0 200 500 0 0

Further types and sizes of casings can be found in the Curaflex product range (see notes on combination of the HKD and DOYMA product range).

The HKD range is excluded from the DOYMA 25-year warranty.