


HKD floor drain

For areas without traffic

- Use in **unfinished floor slabs to be made of waterproof concrete** (white tank)



Floor drain with foil flange



Stainless steel grating




Stainless steel grating, screwed in



Extension piece



Extension of stacking frame



APP-PU 50

HKD floor drain with wall collar for connecting DN 100 KG/ KG 2000 sewer pipes and DN 50 pipes.

- Floor drain/cellar drain made of PP in accordance with DIN EN 1253
- Frame size 150 × 150 mm
- Pipe connection DN 100 (outer diameter 110 mm) and DN 50
- All-round gas and water-tight multi-strip seal
- Vertical outlet
- Flow rate 1.7 l/s
- Height adjustable 15–70 mm
- With lip seal, protective cover for construction phase and sludge trap
- Rotatable and continuously height-adjustable top section
- With odour trap, water seal head 50 mm
- With slotted grating 140 × 140 mm made of plastic, grey
- Alternatively: stainless steel grating made of V2A
- Load class K 3 (300 kg)
- Optionally also available with foil flange for connecting moisture barriers in the form of tanking membranes



ACCESSORIES

- One-component polyurethane sealant material APP-PU 50 with a very good adhesion to steel, plastics and concrete.

HKD floor drain	Article number
HKD floor drain	8 00 0 000 000 1 0
With frost-proof odour trap	8 00 0 000 000 2 0
With foil flange	8 00 0 000 000 1 1
With foil flange and frost-proof odour trap	8 00 0 000 000 2 1

OPTIONAL ACCESSORIES

Stainless steel grating	Article number
Separate	8 99 0 000 000 0 1
Screwed in, with matching stacking frame, 9–67 mm	8 99 0 000 000 0 2

Extension piece	Article number
25–130 mm, can be cut to size	8 99 0 000 000 0 3

Extension of stacking frame	Article number
10–180 mm, can be cut to size	8 99 0 000 000 0 4

APP-PU 50	Article number
Accessories for foil flanges	8 99 0 050 000 0 0

Further information can be found on the HKD APP-PU 50 product page.

The HKD range is excluded from the DOYMA 25-year warranty.

