

Link-Seal BC, BS316

Link chains for plastic pipes

PRESSING WATER

- Sealing of penetrations
- Use in **on-site casing** or **waterproof concrete core bore** (white tank)
- Split version, for **pipes that are already installed**



PRODUCT ADVANTAGES

- Especially suitable for plastic pipes
- Quick installation thanks to pre-assembled system
- Robust rubber parts ensure a long service life
- The radial expansion of the rubber parts ensures a permanent, pressure-tight and secure sealing of the annular space
- Easy installation; even retrofitting possible

TECHNICAL DETAILS


- Leak-tight against pressing water
- For galvanised screws: general application in normal atmosphere, water or humidity. Suitable for electrical insulation and cathodic corrosion protection
- For stainless steel screws: high resistance to water, against most inorganic substances (acids and alkalis) and most organic substances (e.g. acetic acid and acetone)
- LS 200 to LS 275 - FHRK standard 20, 30, 40
- LS 300 to LS 700 - FHRK standard 20, 30, 40, 60

MATERIAL

- Pressure plates: glass fibre reinforced polyamide
- Rubber material: softer EPDM rubber in blue (EPDM 40° ± 5° Shore A)
- Version BC: galvanised steel screws
- Version BS316: A4-70 stainless steel screws



Individual module



The HKD range is excluded from the DOYMA 25-year warranty.

Link-Seal BC (galvanised steel screws)

| Module type/ quantity | Inner diameter [DN in mm] | Outer diameter d [mm] | Article number |
|--------------------------|---------------------------------|--------------------------|--------------------|
| LS200 | – | – | 6 50 0 200 000 0 4 |
| LS265 | – | – | 6 50 0 265 000 0 4 |
| LS275 | – | – | 6 50 0 275 000 0 4 |
| LS300 | – | – | 6 50 0 300 000 0 4 |
| LS310 | – | – | 6 50 0 310 000 0 4 |
| LS315 | – | – | 6 50 0 315 000 0 4 |
| LS325 | – | – | 6 50 0 325 000 0 4 |
| LS340 | – | – | 6 50 0 340 000 0 4 |
| LS360 | – | – | 6 50 0 360 000 0 4 |
| LS400 | – | – | 6 50 0 400 000 0 4 |
| LS410 | – | – | 6 50 0 410 000 0 4 |
| LS425 | – | – | 6 50 0 425 000 0 4 |
| LS440* | – | – | 6 50 0 440 000 0 0 |
| LS475 | – | – | 6 50 0 475 000 0 4 |
| LS500 | – | – | 6 50 0 500 000 0 4 |
| LS525 | – | – | 6 50 0 525 000 0 4 |
| LS575 | – | – | 6 50 0 575 000 0 4 |
| LS625 | – | – | 6 50 0 625 000 0 4 |
| LS700 | – | – | 6 50 0 700 000 0 4 |
| 7x275 | 80 | 40 | 6 50 0 040 080 0 4 |
| 5x340 | 100 | 32 + 40 | 6 50 0 040 100 0 4 |
| 6x315 | 100 | 50 | 6 50 0 050 100 0 4 |
| 7x340 | 125 | 63 | 6 50 0 063 125 0 4 |
| 8x315 | 125 | 75 | 6 50 0 075 125 0 4 |
| 5x410 | 150 | 63 | 6 50 0 063 150 0 4 |
| 9x340 | 150 | 90 | 6 50 0 090 150 0 4 |
| 7x310 | 150 | 110 | 6 50 0 110 150 0 4 |
| 7x475 | 200 | 110 | 6 50 0 110 200 0 4 |
| 9x360 | 200 | 125 | 6 50 0 125 200 0 4 |
| 13x340 | 200 | 140 | 6 50 0 140 200 0 4 |

Link-Seal BS316 (A4-70 stainless steel screws)

| Module type/ quantity | Inner diameter [DN in mm] | Outer diameter d [mm] | Article number |
|--------------------------|---------------------------------|--------------------------|--------------------|
| LS200 | – | – | 6 50 0 200 000 4 4 |
| LS265 | – | – | 6 50 0 265 000 4 4 |
| LS275 | – | – | 6 50 0 275 000 4 4 |
| LS300 | – | – | 6 50 0 300 000 4 4 |
| LS310 | – | – | 6 50 0 310 000 4 4 |
| LS315 | – | – | 6 50 0 315 000 4 4 |
| LS325 | – | – | 6 50 0 325 000 4 4 |
| LS340 | – | – | 6 50 0 340 000 4 4 |
| LS360 | – | – | 6 50 0 360 000 4 4 |
| LS400 | – | – | 6 50 0 400 000 4 4 |
| LS410 | – | – | 6 50 0 410 000 4 4 |
| LS425 | – | – | 6 50 0 425 000 4 4 |
| LS440* | – | – | 6 50 0 440 000 4 0 |
| LS475 | – | – | 6 50 0 475 000 4 4 |
| LS500 | – | – | 6 50 0 500 000 4 4 |
| LS525 | – | – | 6 50 0 525 000 4 4 |
| LS575 | – | – | 6 50 0 575 000 4 4 |
| LS625 | – | – | 6 50 0 625 000 4 4 |
| LS700 | – | – | 6 50 0 700 000 4 4 |
| 7x275 | 80 | 40 | 6 50 0 040 080 4 4 |
| 5x340 | 100 | 32 + 40 | 6 50 0 040 100 4 4 |
| 6x315 | 100 | 50 | 6 50 0 050 100 4 4 |
| 7x340 | 125 | 63 | 6 50 0 063 125 4 4 |
| 8x315 | 125 | 75 | 6 50 0 075 125 4 4 |
| 5x410 | 150 | 63 | 6 50 0 063 150 4 4 |
| 9x340 | 150 | 90 | 6 50 0 090 150 4 4 |
| 7x310 | 150 | 110 | 6 50 0 110 150 4 4 |
| 7x475 | 200 | 110 | 6 50 0 110 200 4 4 |
| 9x360 | 200 | 125 | 6 50 0 125 200 4 4 |
| 13x340 | 200 | 140 | 6 50 0 140 200 4 4 |

Further material combinations available upon request./**black rubber