

Link-Seal C, S316

Link chains for steel/cast iron pipes

PRESSING WATER

- Sealing of penetrations
- Use in **on-site casing** or **waterproof concrete core bore** (white tank)
- Split version, for **pipes that are already installed**



PRODUCT ADVANTAGES

- Quick installation thanks to pre-assembled system
- Robust rubber parts ensure a long service life
- The radial expansion of the rubber parts ensures a permanent, pressure-tight and secure sealing of the annular space
- Oil, fuel and solvent-resistant or high-temperature resistant versions and versions with KTW approval are available
- Easy installation; even retrofitting possible

TECHNICAL DETAILS


- Certified under FHRK test regulation GE 101 (no. G 30 322-6-2)
- Leak-tight against pressing water
- For galvanised screws: general application in normal atmosphere, water or humidity. Suitable for electrical insulation and cathodic corrosion protection
- For stainless steel screws: high resistance to water, against most inorganic substances (acids and alkalis) and most organic substances (e.g. acetic acid and acetone)
- LS 200 to LS 275 - FHRK standard 20, 30, 40
- LS 300 to LS 700 - FHRK standard 20, 30, 40, 60

MATERIAL

- Pressure plates: glass fibre reinforced polyamide
- Rubber material: black EPDM rubber
- Version C: galvanised steel screws
- Version S316: A4-70 stainless steel screws



Individual module



The HKD range is excluded from the DOYMA 25-year warranty.

Link-Seal C (galvanised steel screws)

| Module type/ quantity | Inner diameter [DN in mm] | Outer diameter d [mm] | Article number |
|--------------------------|---------------------------------|--------------------------|--------------------|
| LS200 | – | – | 6 50 0 200 000 0 0 |
| LS265 | – | – | 6 50 0 265 000 0 0 |
| LS275 | – | – | 6 50 0 275 000 0 0 |
| LS300 | – | – | 6 50 0 300 000 0 0 |
| LS310 | – | – | 6 50 0 310 000 0 0 |
| LS315 | – | – | 6 50 0 315 000 0 0 |
| LS325 | – | – | 6 50 0 325 000 0 0 |
| LS340 | – | – | 6 50 0 340 000 0 0 |
| LS360 | – | – | 6 50 0 360 000 0 0 |
| LS400 | – | – | 6 50 0 400 000 0 0 |
| LS410 | – | – | 6 50 0 410 000 0 0 |
| LS425 | – | – | 6 50 0 425 000 0 0 |
| LS440 | – | – | 6 50 0 440 000 0 0 |
| LS475 | – | – | 6 50 0 475 000 0 0 |
| LS500 | – | – | 6 50 0 500 000 0 0 |
| LS525 | – | – | 6 50 0 525 000 0 0 |
| LS575 | – | – | 6 50 0 575 000 0 0 |
| LS615 | – | – | 6 50 0 615 000 0 0 |
| LS650 | – | – | 6 50 0 650 000 0 0 |
| 6x315 | 100 | 48 | 6 50 0 048 100 0 0 |
| 6x300 | 100 | 58 + 60 | 6 50 0 060 100 0 0 |
| 5x360 | 125 | 42 + 48 | 6 50 0 048 125 0 0 |
| 7x340 | 125 | 60 | 6 50 0 060 125 0 0 |
| 8x315 | 125 | 76 | 6 50 0 076 125 0 0 |
| 5x410 | 150 | 58 + 60 | 6 50 0 060 150 0 0 |
| 9x340 | 150 | 89 | 6 50 0 089 150 0 0 |
| 10x315 | 150 | 98 | 6 50 0 098 150 0 0 |
| 7x310 | 150 | 110 | 6 50 0 110 150 0 0 |
| 10x265 | 150 | 114 | 6 50 0 114 150 0 0 |
| 7x475 | 200 | 110 | 6 50 0 110 200 0 0 |
| 7x410 | 200 | 114 | 6 50 0 114 200 0 0 |
| 13x340 | 200 | 135 | 6 50 0 135 200 0 0 |
| 7x400 | 250 | 168 | 6 50 0 168 250 0 0 |
| 7x500 | 300 | 160 | 6 50 0 160 300 0 0 |
| 12x410 | 300 | 210 + 219 | 6 50 0 219 300 0 0 |
| 15x360 | 300 | 222 | 6 50 0 222 300 0 0 |
| 18x360 | 350 | 273 | 6 50 0 273 350 0 0 |

Further material combinations available upon request.

Link-Seal S316 (A4-70 stainless steel screws)

| Module type/ quantity | Inner diameter [DN in mm] | Outer diameter d [mm] | Article number |
|--------------------------|---------------------------------|--------------------------|--------------------|
| LS200 | – | – | 6 50 0 200 000 4 0 |
| LS265 | – | – | 6 50 0 265 000 4 0 |
| LS275 | – | – | 6 50 0 275 000 4 0 |
| LS300 | – | – | 6 50 0 300 000 4 0 |
| LS310 | – | – | 6 50 0 310 000 4 0 |
| LS315 | – | – | 6 50 0 315 000 4 0 |
| LS325 | – | – | 6 50 0 325 000 4 0 |
| LS340 | – | – | 6 50 0 340 000 4 0 |
| LS360 | – | – | 6 50 0 360 000 4 0 |
| LS400 | – | – | 6 50 0 400 000 4 0 |
| LS410 | – | – | 6 50 0 410 000 4 0 |
| LS425 | – | – | 6 50 0 425 000 4 0 |
| LS440 | – | – | 6 50 0 440 000 4 0 |
| LS475 | – | – | 6 50 0 475 000 4 0 |
| LS500 | – | – | 6 50 0 500 000 4 0 |
| LS525 | – | – | 6 50 0 525 000 4 0 |
| LS575 | – | – | 6 50 0 575 000 4 0 |
| LS615 | – | – | 6 50 0 615 000 4 0 |
| LS650 | – | – | 6 50 0 650 000 4 0 |
| 6x315 | 100 | 48 | 6 50 0 048 100 4 0 |
| 6x300 | 100 | 58 + 60 | 6 50 0 060 100 4 0 |
| 5x360 | 125 | 42 + 48 | 6 50 0 048 125 4 0 |
| 7x340 | 125 | 60 | 6 50 0 060 125 4 0 |
| 8x315 | 125 | 76 | 6 50 0 076 125 4 0 |
| 5x410 | 150 | 58 + 60 | 6 50 0 060 150 4 0 |
| 9x340 | 150 | 89 | 6 50 0 089 150 4 0 |
| 10x315 | 150 | 98 | 6 50 0 098 150 4 0 |
| 7x310 | 150 | 110 | 6 50 0 110 150 4 0 |
| 10x265 | 150 | 114 | 6 50 0 114 150 4 0 |
| 7x475 | 200 | 110 | 6 50 0 110 200 4 0 |
| 7x410 | 200 | 114 | 6 50 0 114 200 4 0 |
| 13x340 | 200 | 135 | 6 50 0 135 200 4 0 |
| 7x400 | 250 | 168 | 6 50 0 168 250 4 0 |
| 7x500 | 300 | 160 | 6 50 0 160 300 4 0 |
| 12x410 | 300 | 210 + 219 | 6 50 0 219 300 4 0 |
| 15x360 | 300 | 222 | 6 50 0 222 300 4 0 |
| 18x360 | 350 | 273 | 6 50 0 273 350 4 0 |