

HKD DOMO-DW-B

PRESSING WATER

- Use in **on-site casing** or **waterproof concrete core bore** (white tank)



The HKD DOMO-DW-B features robust craftsmanship quality.
Supplied as a plug seal for safe sealing of an opening.

- Certified under FHRK test regulation GE 101 (no. G 30 322-2-6)
- Leak-tight against pressing water (40 mm seal width)
- All metal parts made of stainless steel 1.4301 (V2A/Inox 304), optionally 1.4571 (V4A/Inox 316)
- Seal material is solid EPDM rubber, optionally NBR
- Gas-tight



ACCESSORIES

- Aquagard core bore sealant, see Curaflex® accessories

The HKD range is excluded from the DOYMA 25-year warranty.

HKD DOMO-DW-B

Inner diameter of casing/core bore [DN in mm]	V2A	V4A
	Article number	Article number
80 (79–83)	8 03 0 000 080 2 0	8 03 0 000 080 4 0
100 (99–103)	8 03 0 000 100 2 0	8 03 0 000 100 4 0
125 (124–128)	8 03 0 000 125 2 0	8 03 0 000 125 4 0
150 (149–153)	8 03 0 000 150 2 0	8 03 0 000 150 4 0
200 (199–204)	8 03 0 000 200 2 0	8 03 0 000 200 4 0
250 (247–253)	8 03 0 000 250 2 0	8 03 0 000 250 4 0
300 (297–304)	8 03 0 000 300 2 0	8 03 0 000 300 4 0
350 (347–353)	8 03 0 000 350 2 0	8 03 0 000 350 4 0
400 (397–403)	8 03 0 000 400 2 0	8 03 0 000 400 4 0
450 (447–453)	8 03 0 000 450 2 0	8 03 0 000 450 4 0
500 (497–503)	8 03 0 000 500 2 0	8 03 0 000 500 4 0
600 (597–603)	8 03 0 000 600 2 0	8 03 0 000 600 4 0

All of the special seals deviating from the standard are delivered as type HKD DISO with 40 mm EPDM elastomer, with 2 × 40 mm EPDM elastomer for DN 800 and higher, for pressing and non-pressing water, and in stainless steel 1.4301 (V2A/Inox 304). The HKD DISO is optionally also available in stainless steel 1.4571 (V4A/Inox 316) and with other elastomer compounds, such as NBR.