


Quadro-Sicura® ADS

for buildings without basements

 PRESSING WATER

- Single-compartment house lead-in as a **round version**
- Use in **unfinished structures made of waterproof concrete**
- For building services **gas or water**
- House lead-ins with **larger dimensions**



PRODUCT ADVANTAGES

- Regulation-compliant floor slab penetration
- Easy installation
- Bend-resistant jacket pipes for compliance with bending radii
- Subsequent replacement of pipes possible (relining)

TECHNICAL DETAILS

- Leak-tight against gas and pressing water
- Suitable for immediate installation in the floor slab or for later retrofitting in a cut-out in the floor slab
- One installation part, consisting of house lead-in combination from Schuck including tear-off protection and anti-twist protection, as well as pre-assembled gasket inserts
- Cast-in part consisting of plastic casing and one connecting sleeve including integrated bend-resistant jacket pipe and height-adjustable rod

Type/version	House lead-in combination [DN]	Plastic casing [DN]	Inner diameter of jacket pipe [mm]
Quadro-Sicura® ADS gas/water	50	100	110
Quadro-Sicura® ADS gas/water	80	150	150

Further dimensions and versions available upon request.

DN of house lead-in combination
50
80

Equipped with 3 m bend-resistant jacket pipe.



Variant: Quadro-Sicura® ADS cast-in part with bend-resistant jacket pipe (inner diameter 110 mm) and Curaflex Nova® sealing system for line diameters up to max. 63 mm. Further designs available upon request.

The Quadro-Sicura ADS system is excluded from the DOYMA 25-year warranty.

