


# Quadro-Sicura® ADS

for building with basements

 PRESSING WATER

- Single-compartment house lead-in **with sealing on both sides**
- Use in **on-site casing** or **waterproof concrete core bore** (white tank)
- For building services **gas** or **water**
- House lead-ins with **larger dimensions**



Quadro-Sicura®  
ADS gas



Quadro-Sicura®  
ADS water

## PRODUCT ADVANTAGES

- Easy installation
- Permanently sealed – no need to re-tension later (maintenance-free)
- Weather-proof installation

## TECHNICAL DETAILS

- Leak-tight against gas and pressing water
- House lead-in combination from Schuck including tear-off protection and anti-twist protection, as well as pre-assembled gasket inserts
- Extraction and torsion safety in accordance with DVGW VP 601
- Installation optionally in accordance with DIN 18195/ DIN 18533

| Type/version                 | House lead-in combination [DN] | Building Wall thicknesses [mm] | Inner diameter of core bore/casing [mm] |
|------------------------------|--------------------------------|--------------------------------|---|
| Quadro-Sicura® ADS gas/water | 50                             | 240–700                        | 99–103                                  |
| Quadro-Sicura® ADS gas/water | 80                             |                                | 149–153                                 |
| Quadro-Sicura® ADS gas/water | 100                            |                                | 199–203                                 |
| Quadro-Sicura® ADS gas/water | 150                            |                                | 249–253                                 |

Further dimensions and versions available upon request.

| DN of house lead-in combination |
|---------------------------------|
| 50                              |
| 80                              |
| 100                             |
| 150                             |